

AR-M9926

19" 1U Rackmount



Features

1 U Rackmount Firewall Server with VIA Nelemlah CPU, 4LANs, Compact Flash, Mini PCI, PCI Slot, USB

VIA 1GHZ

2 USB

4 LAN

CF

Mini PCI

HDD Bay

Xfire.acrosser.com.tw

Specification

System:

CPU	VIA C3
Max. Speed	1 GHz
Chipset	VIA PLE133T+VT82C686B, FSB 66/100MHz
BIOS	AMI

Memory:

Technology	PC-133 SDRAM
Max. Capacity	256MB (Max. 512 MB)
Socket	144-Pin SO-DIMM

Ethernet:

Interface	10/100Mbps Base-T
Controller	NS 83816 x 4
Connector	RJ-45 x 4

Drive Bay:

3.5" HDD	1 (Option)
----------	------------

Cooling:

System FAN	2 (10.8 CFM)
CPU FAN	1

I/O Interface:

	Internal Interface	External Interface
USB		2 (USB 1.1 compliant)
Serial	1 (RS232)	1 (RS232)
Mini PCI Interface	1 (3.3V Mini PCI connector)	
Expansion Interface	1 (32-bit PCI Expansion Slot)	
PS/2	Mouse x 1, Keyboard x 1	
GPIO	One TTL 8-bit input	
Control		Power Switch
Solid State Disk	1 (Compact Flash Type I)	

Management:

Indicator	8 LEDs for Network connector as ACT and Link
-----------	--

Miscellaneous:

Watchdog Timer	Software programmable 1~63 seconds
----------------	------------------------------------

Environment:

Operating Temperature	0 ~ 40°C (32 ~ 104 °F)
Storage Temperature	-20 ~ 80°C (-4 ~ 176 °F)
Operating Humidity	0 ~ 90% Relative humidity non-condensing
Power Requirement	44W Internal Power Supply

Physical:

Form Factor	19", 1U Rackmount
Dimension (W x D x H)	440mm x 210mm x 44mm(17.3" x 8.27" x 1.7")

Packing List:

190030160	3.5" HDD Cable
190030388	DB-9 to DB-9 Console Cable
170010444	Mount Bracket
170020011	Mount Bracket Fixed screws M3*6mm*8
	Utility CD, Manual

Ordering Information

Standard:

AR-M9926	1 U Rackmount Firewall Server with VIA Nelemlah CPU, 4LANs, Compact Flash, Mini PCI, PCI Slot, USB
----------	--

Option:

190030370	3.5" HDD Cable
190030195	Keyboard/Mouse Cable

Specifications are subject to change without notice.