

AR-M9921

Embedded System



Features

GX 1 fanless and dust proof micro embedded system

Fanless >

GX 1 >

SDRAM >

Audio >

2 LAN >

4 COM >

CF (Option) >

DOC >

Specification

General:

Construction	Aluminum Micro Box
Dimension (W x D x H)	216mm x 240mm x 66mm (8.5" x 9.4" x 2.6")
Front Panel	1. One Mic, Line-in, Line-out and Speaker out connector 2. Two USB ports 3. Power LED
Rear Panel	1. Four Serial ports, One VGA port and Two LAN ports 2. One printer port 3. KB/Mouse connector 4. DC power jack

Power Adapter:

Input Voltage	90~260V
Input Frequency	47~63Hz
Output Rating	27W
Output Voltage	+5V @ 3A, +12V @ 1A

Packiing list:

150010045	Power 27W AC100V/240V (PW-027A-2YB1) AR-B1662
190030129	IDC2.0 Cable with Female Connector (44P*2 210mm)
	Utility CD, Manual

System:

CPU Board	AR-B1565 (5.25" CPU Board)
System Memory	Max. memory Up to 256MB
Enhanced IDE	Supports 2.5" HDD
Ethernet	Realtek RTL8100B, support 10/100Mbps Base-T with RJ45x2
Serial Port	3xRS-232, 1xRS-232C/485
Video	VGA Port with DB15 Connector
Expansion Interface	One 16-bit PC/104 bus
SSD	Supports one DiskOnChip (DOC) socket

Ordering Information

Standard:

AR-M9921	GX1 Fanless and Dust Proof Micro Embedded System
----------	--

Option:

190020012	AC Power Cord (EU Type, 2.5A 1830mm Black (C043))
190020013	AC Power Cord (USA Type, 10A 1830mm Black (C032))
190020014	AC Power Cord (UK Type+Fuse, 13A 1800mm Black (C047))
190020015	AC Power Cord (AU Type, 2.5A 1830mm Black)
010020212	AR-B9462C, IDE to Compact Flash Adaptor

Specifications are subject to change without notice.