



Main

Range of product	Modicon Premium Automation platform
Product or component type	Discrete input module
Discrete input number	64 current sink isolated EN/IEC 61131-2 type 1
Discrete input voltage	24 V DC positive
Electrical connection	HE-10 connector
Protective treatment	TC

Complementary

Sensor power supply	19...30 V
Discrete input current	3.5 mA
Voltage state 1 guaranteed	≥ 11 V
Current state 1 guaranteed	≥ 3 mA
Voltage state 0 guaranteed	≤ 5 V
Current state 0 guaranteed	≤ 1.5 mA
Input impedance	6300 Ohm at state 1
Response time	4 ms ≤ 7 ms
Insulation resistance	< 10 MOhm 500 V DC
Power dissipation	(1.5 W + 0.1 W x No of channels used)
Marking	CE
Current consumption	155 mA 5 V DC 315 mA 24 V DC
Module format	Standard
Product weight	0.37 kg

Environment

Dielectric strength	1500 V AC 50/60 Hz
Standards	73/23/EEC 89/336/EEC 92/31/EEC 93/68/EEC CSA 22-2 No 142 CSA 22-2 No 213 Class I Division 2 Group A CSA 22-2 No 213 Class I Division 2 Group B CSA 22-2 No 213 Class I Division 2 Group C CSA 22-2 No 213 Class I Division 2 Group D EN/IEC 61131-2 IEC 60664 UL 508
Product certifications	ABS BV DNV (Det Norske Veritas) GL LR RINA RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Relative humidity	5...95 % without condensation for storage 10...95 % without condensation for operation
Operating altitude	0...2000 m
IP degree of protection	IP20
Pollution degree	2
RoHS EUR conformity date	0847
RoHS EUR status	Compliant