


FSB-868G

Computing Platform Service Partner

Intel® Pentium® D LGA775 PICMG Full-size SBC



Features

- Supports Intel® Pentium® 4/ Pentium® D LGA775 CPUs up to 3.8GHz (Dual Core CPU)
- DDR II 667 Memory Supports up to 4GB
- Integrated GMA950 2D/3D Graphics Accelerator, VGA Support
- Supports Dual Channel LVDS Output (Optional)
- Supports 10/100/1000Base-TX Ethernet (Optional) x 2
- Supports Ultra ATA100 & SATA II x 4 & CompactFlash™ Type-II Storage
- 7 USB 2.0/ 2 RS-232/422/485/ 1 Parallel/ 1 IrDA Ports
- Watchdog Function 1~255 Sec.

Specifications

System	
Form Factor	PICMG Full-size SBC
Processor	Intel® Pentium® 4 up to 3.8 GHz/ Pentium® D up to 3.6GHz/ Celeron® D up to 3.46 GHz, LGA 775 Package, FSB 533/800/1066 MHz
System Memory	2 x 240-pin 1.8V DDR2 DIMM Socket, total up to 4GB Support Dual Channel DDR memory (DDRII 533/667)
Chipset	Intel® 945G + Intel® 82801GB (ICH7/ ICH7R RAID optional)
Ethernet	2 x PCI Express 10/100Mb or 10/100/1000Mb LAN with RJ-45 connectors Marvell 88E8036/88E8053 controller
BIOS	Award Plug & Play FWH BIOS-4Mb ROM
IDE Interface	1 x ATA-100 (Supports CD-ROM ATAPI device) 4 x SATA 3Gb/s (Support four SATA devices)
SSD	1x CFD type II Connector
Expansion Interface	ISA/ PCI/ PCI Express Connector (DF13-30P)
Watchdog Timer	1~255 Sec. can be set with software on Super I/O
RTC	Internal RTC
Battery	Lithium Battery
Power Requirement	ATX, ATX12V
Operating Temperature	32°F~140°F (0°C ~ 60°C)
Board Size	13.3"(L) x 4.8"(W) (338mm x 122mm)
Gross Weight	1.2 lb (0.5 kg)
MTBF (Hours)	65,000
Power Consumption (Typical)	176W, with Pentium® 4 3.8GHz/ FSB 800MHz/ 2MB L2 Cache
EMC	CE/ FCC Class A
Display	
VGA Controller	Integrated VGA on Intel® 945G, Core frequency up to 400MHz
Memory	Share memory up to 256MB
Resolutions	CRT: up to 2048 x 1536 @ 32bpp LCD: up to 1600 x 1200 @ 24-bit
LCD Interface	18/24-bit LVDS, 36/48-bit support
I/O	
IR Interface	Supports One IrDA Header
Audio (Daughter Board)	Realtek ALC655 AC97 Codec, MIC-in/Line-in/Line-out/CD-in optional
Floppy Disk Interface	1 x Standard Floppy Disk Drive
Serial Port	2 x COM Ports: (Internal Pin Header, External D-sub x 2) COM 1: RS-232 COM 2: RS-232/ 422/ 485
Parallel port	1 x Parallel port supports SPP/ EPP/ ECP mode
Keyboard and Mouse	1 x Mini-DIN PS/2 keyboard and Mouse connector 1 x internal keyboard pin header
Universal Serial Bus	7 x USB 2.0 Ports 3 Internal 5x2-pin headers support up to 6 USB ports 1 x TYPE-A Connector onboard




Packing List

- **1701340704**
Flat Cable, 34P, 70cm, GRAY for Floppy Disk Drive
- **1701400453**
Cable, 40P 2.54mm IDC w/Nose w/Fold, 40P 2.54mm IDC w/ Nose w/Fold, 45cm, Blue ATA-100, B016-009-2
- **1700060192**
Cable, 6P-6P-6P, 19cm, IVORY PS2/ Keyboard&Mouse
- **1701260307**
Flat Cable, 9P/DB9P MALE&25P DB25P FEMALE, 10P 2mm & 26P 2mm/IDC NO FOLD, 30cm, W/BKT, A002-015
- **1701100305**
Flat Cable, 9P/DB9P MALE, 10P/2.0mm Pitch/ IDC NO FOLD, 30cm, W/BACKET
- **1703030501**
Wire, 3P 2.5mm Housing, 3P 2.5mm Housing, 50cm
- **1709100201**
USB Cable, 20cm 2.0mm, W/Bracket
- **1709070780**
4 SATA CABLES, 7P Pitch 1.27mm, 78cm
- **1759200161**
CPU Cooler Fan, for LGA775 Pentium® 4 3.6G, 4P, 12V, Dual ball bearing, LGA-775-91502
- **21304866G0**
Sponge, FSB-866G, 400x185x10 mm, Black
- **211866G001**
Inside Box, FSB-866G, 120x80x88 mm
- **Quick Installation Guide**
- **Utility CD**
- **FSB-868G**

Ordering Information

- **TF-FSB-868G-A10-V**
Full Size PICMG CPU Card, Socket 775 Pentium® 4, VGA, 7 USB, CF, Audio, 4 SATA, Rev. A1.0
- **TF-FSB-868G-A10-VE**
Full Size PICMG CPU Card, Socket 775 Pentium® 4, VGA, 10/100M LAN, 7 USB, CF, Audio, 4 SATA, Rev. A1.0
- **TF-FSB-868G-A10-VG**
Full Size PICMG CPU Card, Socket 775 Pentium® 4, VGA, 10/100/1000M LAN, 7 USB, CF, Audio, 4 SATA, Rev. A1.0
- **TF-FSB-868G-A10-EG**
Full Size PICMG CPU Card, Socket 775 Pentium® 4, VGA, 10/100M & 10/100/1000M LAN, 7 USB, CF, Audio, 4 SATA, Rev. A1.0
- **TF-FSB-868G-A10-E2**
Full Size PICMG CPU Card, Socket 775 Pentium® 4, VGA, 2 10/100M LAN, 7 USB, CF, Audio, 4 SATA, Rev. A1.0
- **TF-FSB-868G-A10-G2**
Full Size PICMG CPU Card, Socket 775 Pentium® 4, VGA, 2 10/100/1000M LAN, 7 USB, CF, Audio, 4 SATA, Rev. A1.0
- **TF-FSB-868G-A10-G2LV**
Full Size CPU Card, LGA 775 Pentium® D, VGA, 2 10/100/1000M LAN, 7 USB, CF, AC97, 4 SATA, LVDS, Rev. A1.0
- **TF-FSB-868G-A10-RF**
Full Size CPU Card, LGA 775 Pentium® D, VGA, 2 10/100/1000M LAN, 7 USB, CF, AC97, 4 SATA II, LVDS, Raid, Rev. A1.0

Dimension Unit: mm



Passive Backplane Options

P/N	Description	Master Interface	Slots	Power Connector, ATX Extend Function
TF-BP-213RG-P4-A11	Rackmount, PICMG, 13-slot R.PCI Backplane, 4 PCI/7 ISA, Single Segment, AT/ATX, Rev. A1.1	PICMG	4/8/2 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-2145G-P4-A11	Rackmount, PICMG, 14-slot Backplane, 4 PCI/8 ISA, Single Segment, AT/ATX, Rev. A1.1	PICMG	4/9/2 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-2145G-P7-A11	Rackmount, PICMG, 14-slot Backplane, 7 PCI/5 ISA, Single Segment, AT/ATX, Rev. A1.2	PICMG	7/6/2 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-2145G-P12-A11	Rackmount, PICMG, 14-slot Backplane, 12 PCI/1 ISA Single Segment, AT/ATX, Rev. A1.1	PICMG	12/2/2 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-2085G-P4-A11	Wallmount, PICMG, 8-slot Backplane, 4 PCI/2 ISA, Single Segment, AT/ATX, Rev. A1.1	PICMG	4/3/2 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-2085G-P7-A11	Wallmount, PICMG, 8-slot Backplane, 7 PCI/0 ISA, Single Segment, AT/ATX, Rev. A1.1	PICMG	7/0/1 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-206VG-P4-A11	Rackmount, PICMG, 6-slot Backplane, 4 PCI/0 ISA, Single Segment, AT/ATX, Rev. A1.1	PICMG	4/0/1 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-206VG-P2-A10	Rackmount, PICMG, 6-slot Backplane, 2 PCI/3 ISA, Single Segment, ATX, Rev. A1.0	PICMG	2/3/1 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-2065G-P4-A11	Wallmount, PICMG, 6-slot Backplane, 4 PCI, 2 ISA, Single Segment, ATX, Rev. A1.1	PICMG	4/2/2 (PCI/ISA/PICMG)	AT, ATX, 3-pin ATX extend
TF-BP-2065G-P3-A11	Wallmount, PICMG, 6-slot Backplane, 3 PCI, 3 ISA, Single Segment, ATX, Rev. A1.0	PICMG	3/3/2 (PCI/ISA/PICMG)	ATX, 3-pin ATX extend

Optional Accessories

- TF-TF-PER-C101**
 Dual PCI-E Giga LANs Card w/Broadcom BCM 5789/5751/5721
- TF-TF-PER-C102**
 Dual PCI-E 10/100/1000 LANs Card w/Marvell 88B8036/53
- TF-TF-PER-U00A**
 5.1 Channel Audio 4 USB Connectors
- TF-TF-PER-U00H**
 7.1 Channel Audio
- 1703030501**
 Supports ATX Power from Backplane to CPU Card
- 1702030301**
 ATX Power Simulation AT Power Switch Wire
- 1701400800**
 P-ATA100 Cable 80cm
- 1709070780**
 Signal Cable 78cm
- 1702043000**
 ATX 12V Extension Cable
- 1701260307**
 1 Serial port + 1 Parallel port with Bracket
- 1701100305**
 1 Serial port with Bracket
- 1998666611**
 P-ATA IDE removable frame-Black
- 1998666612**
 P-ATA IDE removable frame-White
- 1998666613**
 SATA IDE removable frame-Black
- 1998666614**
 SATA IDE removable frame-White
- 1759200162**
 CPU Cooler Fan for LGA775 Pentium® 4, 3.8GHz, 3P 12V, Dual Ball Bearing, 2 U.