




F225 Line Circuit Breakers

70-250 Amperes-TFJ Noninterchangeable Trip
70-225A TFK, THFK Interchangeable Trip
480 or 600 volts AC
250 Volts DC

Note: All TFJ, TFK and THFK breakers are UL listed as HACR.



Frame



Type TFK

Type TFJ—Noninterchangeable Trip

Includes line and load lugs. Suitable for reverse feed.

Ampere Rating	Adjustable Trip Range Amp		Complete Breaker 480 Vac Max.		Complete Breaker 600 Vac Max.		Copper/Aluminum Lugs	Wire Size		
	Lo	Hi	Catalog Number	List Price, GO-135B	Catalog Number	List Price, GO-135B				
Two-Pole					Three-Pole					
70	600	900	TFJ224070WL	\$1122.00	TFJ236070WL	\$1407.00	TCAL24	#4-300 kcmil		
80	700	1000	TFJ224080WL	1122.00	TFJ236080WL	1407.00				
90	600	900	TFJ224090WL	1122.00	TFJ236090WL	1407.00				
100	600	1250	TFJ224100WL	1122.00	TFJ236100WL	1407.00				
110	660	1250	TFJ224110WL	1122.00	TFJ236110WL	1407.00				
125	600	1250	TFJ224125WL	1122.00	TFJ236125WL	1407.00				
150	700	1500	TFJ224150WL	1122.00	TFJ236150WL	1407.00				
175	800	1750	TFJ224175WL	1122.00	TFJ236175WL	1407.00				
200	900	2000	TFJ224200WL	1122.00	TFJ236200WL	1407.00				
225	1000	2250	TFJ224225WL	1122.00	TFJ236225WL	1407.00				
250	1000	2250	—	—	TFJ236250WL	2075.00			®	®
225NA	—	—	TFJ226Y225®®	803.00	TFJ236Y225®®	1174.00			TCAL24	—

Types TFK, THFK—Interchangeable Trip

Ampere Rating	Adjustable Trip Range Amp		Complete Circuit Breaker Includes Line and Load Lugs				Trip Unit Only		Frame Only		Terminal Lugs for Front Connection (Copper/Aluminum)®		
	Lo	Hi	Standard		Hi-Break*		Use with Standard and Hi-Break Frames	List Price, GO-135B	Catalog Number	List Price, GO-135B	Catalog Number (Order 1 line and 1 load per pole)	List Price, GO-135B	Wire Size
			Catalog Number	List Price, GO-135B	Catalog Number	List Price, GO-135B							

Two-Pole, 480 Volts AC Max., 250 Volts DC Max.

70	600	900	TFK224070WL	\$1122.00	THFK224070WL	\$2315.00	TFK226T070	\$337.00	TFK224F000 Standard Frame	\$753.00	TCAL24	\$8.00	#4-300 kcmil					
80	700	1000	TFK224080WL	1122.00	THFK224080WL	2315.00	TFK226T080	337.00										
90	600	900	TFK224090WL	1122.00	THFK224090WL	2315.00	TFK226T090	337.00										
100	600	1250	TFK224100WL	1122.00	THFK224100WL	2315.00	TFK226T100	337.00										
110	660	1250	TFK224110WL	1122.00	THFK224110WL	2315.00	TFK226T110	337.00										
125	600	1250	TFK224125WL	1122.00	THFK224125WL	2315.00	TFK226T125	337.00										
150	700	1500	TFK224150WL	1122.00	THFK224150WL	2315.00	TFK226T150	337.00										
175	800	1750	TFK224175WL	1122.00	THFK224175WL	2315.00	TFK226T175	337.00										
200	900	2000	TFK224200WL	1122.00	THFK224200WL	2315.00	TFK226T200	337.00										
225	1000	2250	TFK224225WL	1122.00	THFK224225WL	2315.00	TFK226T225	337.00										
225NA	—	—	TFK226Y225®®	937.00	—	—	TFKY2®	148.00						THFK224F000 Hi-Break Frame	1946.00	—	—	—

Three-Pole, 600 Volts AC Max., 250 Volts DC Max.

70	600	900	TFK236070WL	1407.00	THFK236070WL	2787.00	TFK236T070	445.00	TFK236F000 Standard Frame	914.00	TCAL24	8.00	#4-300 kcmil					
80	700	1000	TFK236080WL	1407.00	THFK236080WL	2787.00	TFK236T080	445.00										
90	600	900	TFK236090WL	1407.00	THFK236090WL	2787.00	TFK236T090	445.00										
100	600	1250	TFK236100WL	1407.00	THFK236100WL	2787.00	TFK236T100	445.00										
110	660	1250	TFK236110WL	1407.00	THFK236110WL	2787.00	TFK236T110	445.00										
125	600	1250	TFK236125WL	1407.00	THFK236125WL	2787.00	TFK236T125	445.00										
150	700	1500	TFK236150WL	1407.00	THFK236150WL	2787.00	TFK236T150	445.00										
175	800	1750	TFK236175WL	1407.00	THFK236175WL	2787.00	TFK236T175	445.00										
200	900	2000	TFK236200WL	1407.00	THFK236200WL	2787.00	TFK236T200	445.00										
225	1000	2250	TFK236225WL	1407.00	THFK236225WL	2787.00	TFK236T225	445.00										
225A Mag Only	600	1400	—	—	—	—	TFK236TM1225®	555.00						THFK236F000 Hi-Break Frame	2294.00	—	—	—
	1000	2250	—	—	—	—	TFK236TM2225®	555.00										
225NA	—	—	TFK236Y225®®	1174.00	—	—	TFKY3®	208.00						—	—	—	—	—

CD Molded-case switch. Complete switch includes line and load lugs. UL listed only when ordered as a complete switch.

② Internal accessory installation requires dummy trip unit. See page 16-23 for additional details.

③ Not UL listed.
④ For optional lugs, see page 16-32.
⑤ 600 volts maximum.

® TC024 load end. Wire range #4-300 kcmil copper only.
Accessories:
See pages 16-19 to 16-32.