

PIK-215A/IRC-215N

19" 1U rack-mount keyboard drawer with 101-key keyboard



▲ PIK-215A

▲ IRC-215N

FEATURE

- Smart and compact design for rack-mount application
- 1U (1.75") high for space saving
- Equipped with a 101-key keyboard
- Equipped with a trackball (PIK-215A & IRC-215N only)



▲ PIK-210A

▲ IRC-210N

ORDERING GUIDE

PIK-215A

19" 1U industrial keyboard drawer with a 101-key keyboard and a trackball

IRC-215N

19" 1U industrial keyboard drawer with a 101-key keyboard and a trackball

PIK-210A

19" 1U industrial keyboard drawer with a 101-key keyboard

IRC-210N

19" 1U industrial keyboard drawer with a 101-key keyboard

Keyboard

| | |
|----------------------|-----------------------|
| No. of Keys | 101 |
| Keys Travel | 3.5 mm |
| LED | Num. Cap. Scroll Lock |
| MTBF | >20 million strokes |
| Interface | AT or PS/2 |
| Certification | UL, CE |

Trackball (PIK-215A & IRC-215N only)

| | |
|----------------------|-------------|
| No. of Keys | 3 |
| Compatibility | Microsoft |
| Interface | DB9 or PS/2 |
| Certification | UL, CE |

General

| | |
|------------------------------------|---|
| Construction | Heavy-duty steel panel |
| Standard Color | Beige, Black |
| Drawer Travel | 11" |
| Dimension | 482.8(W) x 341(D) x 44(H) mm 19"(W) x 13.4"(D) x 1.7"(H) |
| Weight | Net: 5.5 kg (12.2 lb); Gross: 6.5 kg (14.4 lb) |
| Operating Temperature Range | 0 to +55°C |
| Storage Temperature Range | 0 to +70°C |
| Relative Humidity | 5% to 95%, non-condensing |

ENGINEERING DRAWING

