FPM-5151G FPM-5171G FPM-5191G

15" XGA / 17" SXGA / 19" SXGA Industrial Monitors with Resistive Touchscreens, Direct-VGA, and DVI Ports



Features

- 15" XGA or 17" / 19" SXGA TFT LCDs
- Direct VGA & DVI-D video input interface
- Lockable OSD keys with 2 user-defined contrast/brightness settings
- Flat-sealed front panel
- Robust design with anti-rust chassis and aluminum die-cast front panel
- Front accessible USB connector
- Combo RS-232 & USB interface for touchscreen function (optional)
- Supports industrial 10-30 V_{DC} power input
- · Supports panel, wall, desktop, rack or VESA arm mounting
- Front panel is NEMA4/IP65 compliant

Introduction

The FPM-5000G series provides 15", 17" and 19" color TFT LCD flat panel monitors specifically designed for industrial applications. With a viewing size from 15" to 19", they present ample display areas as well as vivid and sharp images. It features Direct-VGA & DVI-D signal transmission, which allows VGA control cards to be used in your system. The onscreen display allows users to adjust the images on the screen with two user-defined settings. The front access USB connector provides easy access the controller, and the industrial 10-30 Vdc wide range power support makes this product an excellent option for Factory and Machine Automation display solutions.

Specifications

General

Button Controls OSD control pad on rear side with lockable function

• Certification BSMI, CCC, CE, FCC Class B, UL

Dimensions (WxHxD) 5151G: 449.92 x 315.63 x 50.5 mm (17.71" x 12.43" x 2")

5171G: 481.9 x 355.9 x 55 mm (18.97" x 14.01" x 2.17")

5191G: 481.93 x 384.6 x 59 mm (18.97" x 15.14" x 2.32")

• **Enclosure** Front panel: Aluminum and flat-sealed

Rear cover: Anti-rust coating

• **Mounting** Panel, wall, desktop, VESA arm, or 19" rackmount

■ **Power Input** Phoenix Jack - 10 ~ 30 V_{DC} input

Optional external 57 W power adapter, with AC 100 V \sim 240 V input and DC +12 V @ 4.7A output

Power Consumption
USB
18 W + 20% / 31 W + 20% / 32 W + 20%
Front USB access for extension

• Video Port VGA & DVI-D

• **Weight (Net)** 6 kg (13.22 lbs) / 8 kg (17.63 lbs) / 10 kg (22.04 lbs)

LCD Display

Display Type
XGA/ SXGA/ SXGA TFT LCDs

■ **Display Size** 15"/ 17"/ 19"

Max. Resolution
1024 x 768 / 1280 x 1024 / 1280 x 1024

■ Max. Color 16.2M

• Viewing Angle (H/V°) 160/130, 170/160, 178/178

Luminance (cd/m²) 250 / 380 / 300
Backlight Life (hrs) 50.000

Contrast Ratio
700:1 / 1000:1 / 1300 : 1

Touchscreen (Optional)

Sensor AMT

• **Driver** Penmount 6000

■ **Type** 8-wire / 8-wire / 5-wire Resistive

• Interface RS-232 & USB

Lifespan
10/10/36 million with a silicone rubber of R8 finger,

writing rate is by 250g at 2 times/s

• Light Transmission > 80%

OS Support
Windows 2000, XP, Vista, 7, XPe, CE and Linux

Power Consumption +5 V @ 100 mA
Touch Resolution Linearity

Environment

Operation Temperature 0 ~ 50° C (32 ~ 122° F)
Storage Temperature -20 ~ 60° C (-4 ~ 140° F)
Humidity (Storage) 10 ~ 90% non-condensing

Waterproof
Front panel is NEMA4/IP65 compliant
Vibration
Front panel is NEMA4/IP65 compliant
5 ~ 500 Hz, 1 Grms (Operating, Random)

Ordering Information

■ FPM-5191G-XOAE 19" SXGA Ind. Monitor

• FPM-5191G-R3AE 19" SXGA Ind. Monitor w/Resistive TS (RS-232, USB)


■ FPM-5171G-X0AE 17" SXGA Ind. Monitor

• FPM-5171G-R3AE 17" SXGA Ind. Monitor w/Resistive TS (RS-232, USB)

FPM-5151G-X0AE
15" XGA Ind. Monitor

• FPM-5151G-R3AE 15" XGA Ind Monitor w/Resistive TS (RS-232, USB)

FPM-5151G / FPM-5171G / FPM-5191G



Accessories

■ FPM-5151G-SMKE FPM-5151G/5171G Stand Kit ■ FPM-5191G-SMKE FPM-5191G Stand Kit

■ IPPC-6152A-RMKE IPPC-6152A/FPM-5151G Rack Mount Kit

■ IPPC-6172A-RMKE IPPC-6172A/FPM-5171G Rack Mount Kit ■ IPPC-6192A-RMKE IPPC-6192A/FPM-5191G Rack Mount Kit

1702002600 Power Cable US Plug 1.8 M


1702002605 Power Cable EU Plug 1.8 M **1702031801** Power Cable UK Plug 1.8 M

1702031836 Power Cable China/Australia Plug 1.8 M **1757002742** Adapter AC 90-264V 57W SPU63-105

Front Accessible USB Port



I/O View



Back View

