

HS-7260

Intel® Core™ 2 Duo/Core™ Duo/Core™ Solo/Celeron® M processor PCI-ISA Bus SBC w/CF, DVI-I/CRT/LVDS, Dual GB LAN, Audio, SATA, 4 USB2.0



Features

- Intel® Core™ 2 Duo/Core™ Duo/Core™ Solo/Celeron® M processor 1.66~2.33GHz, supports 667/533MHz FSB
- 1 x SO-DIMM up to 2GB DDR2 SDRAM
- Intel® 945GME/ICH7-M system chipset
- Intel® 945GME integrated VGA for CRT & LVDS
- 2 x 10/100/1000 Mbps ethernet
- AC'97 audio codec
- Supports CF, 2 x SATA, 2 x COM, 4 x USB2.0
- Supports 18-bit LVDS, 8-bit GPIO, H/W Monitor function
- Option for DVI-I display, mini PCIe x1 socket

System

CPU
Intel® Core™ 2 Duo/Core™ Duo/Core™ Solo/Celeron® M processor 1.66~2.33GHz
Core™ 2 Duo: T5500, T5600, T7200, T7400, T7600
Core™ Duo: T2300, T2400, T2500, T2600, T2700
Celeron® M: 410, 420, 430, 440, 450

Bus Interface
PCI-ISA Bus (no 3.3V output through Golden Finger)

FSB
667/533MHz FSB

BIOS
Award PnP Flash BIOS

System Chipset
Intel® 945GME/ICH7-M

I/O Chipset
Winbond W83627EHG

System Memory
1 x 200-pin SO-DIMM socket DDR2 667MHz up to 2GB

Storage
1 x Type II CF socket

Watchdog Timer
Software programmable time-out intervals from 1~255 sec. or 1~255 min.

H/W Status Monitor
Monitoring temperatures, voltages, and cooling fan status

Expansion Interface
1 x mini PCIe x1 socket (option)

Power Function
Supports AT/ATX power mode

Operating Temperature
0~60 degrees C

Operating Humidity
0~95%, non-condensing

Size (L x W)
186 x 122 mm

I/O Interface

- MIO**
- 1 x RS-232
 - 1 x RS-232/422/485
 - 4 x USB2.0 (4 x internal)
 - 1 x IDE
 - 1 x FDD
 - 1 x Parallel
 - 2 x SATA
 - 1 x PS/2 for KB/MS
 - 1 x 6-pin header for PS/2 KB/MS

GPIO
8-bit general purpose input/output port

Display

Chipset
Intel® 945GME integrated Intel® GMA950

LVDS
18-bit single/dual-channel

DVI Chipset
Chrontel 7307 (option)

Resolution
CRT Mode: 2048 x 1536

Audio

Chipset
RealTek ALC202A

Audio Interface (w/pin header)
MIC In, Line Out

Ethernet

Chipset
Dual RealTek RTL8111C 10/100/1000 Mbps LAN

Ethernet Interface
2 x RJ-45

Ordering Guide

HS-7260
Intel® Core™ 2 Duo/Core™ Duo/Core™ Solo/Celeron® M processor SBC w/CF, CRT, Dual GB LAN, Audio

HS-7260/DVI-I
Intel® Core™ 2 Duo/Core™ Duo/Core™ Solo/Celeron® M processor SBC w/CF, DVI-I, Dual GB LAN, Audio

Accessory Options
LVDS Cable, COM Cable, USB Cable, SATA Cable, IDE Cable, FDC Cable, H=23mm CPU Cooler