



## Features

- Supports Intel® Pentium® processor with MMX™ technology
- C&T 69000 LCD controller supports 36-bit TFT Panels
- One 10/100Base-T Fast Ethernet
- Supports DiskOnChip® up to 1GB
- High Drive design to enhance ISA driving capacity

## Specifications

### System

- **CPU** Socket 7 Pentium® processor with MMX™ technology 166- 266MHz, (with system bus frequencies of 66/100MHz)
- **System Memory** SDRAM DIMM x 3, Max. 768MB
- **2<sup>nd</sup> Cache Memory** Onboard 512KB pipeline burst L2 Cache
- **Chipset** ALi 1541/1543
- **I/O Chipset** ALi1543
- **BIOS** Award 256KB FLASH ROM
- **Ethernet** Realtek RTL8139X, 10/100Base-T RJ-45 connector x 1
- **SSD** Supports DiskOnChip® up to 1GB
- **Watchdog Timer** Can generate a system reset, IRQ15 or NMI
- **Expansion Interface** PICMG 2.0
- **Battery** Lithium battery
- **DMA** 7 DMA channels (8237 equivalent)
- **Interrupt** 15 interrupt levels (8259 equivalent)
- **H/W status monitoring** Winbond W83781D H/W status monitoring IC supports power supply voltages, fan speed control and temperature monitoring
- **Power supply voltage** +5V (4.75V to 5.25V), +12V(11.4V to 12.6V),
- **Size/ Weight** AT13.3" (L) x 4.8" (W) (338 mm x 122 mm), 1.2lb. (0.5Kg)
- **Operating temperature** 32°F to 140°F (0°C to 60°C)

### I/O

- **MIO** IDE (UDMA33) x 2, FDD x 1, KB+Mouse x 1, RS-232 x 1, RS-232/422/485 x 1, Parallel x 1
- **IrDA** One IrDA Tx/Rx header
- **USB** One 5x2 pin header supports 2 USB 1.1 ports

### Display

- **Chip** C&T 69000
- **Memory Size** Built-in 2MB SDRAM
- **Resolution** Up to 1024 x 768@ 16bpp colors
- **LCD Interface** 36-bit TFT/DSTN/MONO LCD panel

## Packing List

- IDE cable 1701400601
- FDD cable 1701340700
- COM Port cable kit (1 parallel, 1 serial) 1701260302
- KB/Mouse cable 1700060192
- Quick Installation Guide
- Utility CD