



Features

- 3.5" FDD SubCompact Form Factor
- Onboard Transmeta Crusoe TM5400 600MHz / TM5800 733MHz CPU
- Onboard 64MB SDRAM (16MB for CMS)
- Supports CRT and 36-bit TFT/24-bit DSTN panels, LCD with rotatable display
- Supports Type III Mini PCI socket or two Type II PCMCIA sockets
- 10/100Base-T Fast Ethernet
- Extremely Low power consumption (LongRun™ Technology)
- Low profile design



Specifications

System

- CPU Transmeta Crusoe TM5400 600MHz / TM5800 733MHz
- System memory 64MB SDRAM onboard, 16MB shared for Code Morphing Software. SDRAM SODIMM x 1, Max. 512MB
- Chipset Transmeta Crusoe TM5400/TM5800 + VIA VT82C686B
- I/O Chipset VIA VT82C686B
- BIOS Award 256KB FLASH ROM
- Ethernet RTL 8139DL, 10/100Base-T RJ-45 connector x 1.
- SSD Type II CompactFlash slot
- Watchdog Timer Generate a system reset
- Expansion Interface Type II PCMCIA x2 or type III Mini PCI x 1
- Battery Lithium battery
- Power supply voltage +5V, +12V, AT or ATX. (WIN 2000, WIN XP only)
- Board size 5.75" (L) X 4" (W) (146mm x 101.6mm)
- Gross Weight 0.88 lb. (0.4kg)
- Operating temperature 32°F to 140°F (0°C to 60°C)

I/O

- MIO IDE (UDMA33) x 1, FDD x 1, KB+Mouse x 1, RS-232 x 1, RS-232/422/485 x 1, Parallel x 1
- IrDA One IrDA Tx/Rx header
- Audio VIA VT82C686B + VT1612A Audio CODEC
- USB Two 5x2 pin headers support 4 USB 1.1 ports

Display

- Chip SMI LynxEM+ SM712
- Memory size Built-in 4MB SGRAM
- Resolution up to 1280 X 1024 @ 24bpp for CRT. up to 1024 X 768 @ 24bpp for TFT & DSTN
- LCD Interface up to 36-bit TTL TFT or 16/24 bit DSTN LCD panels
- Dual Display Simultaneous Scan: CRT+LCD: 1024 x 768 @ 24bpp
Dual View: CRT+LCD: 1024x768 @D1 16bpp, D2 8bpp or D1 @8bpp, D2 @24bpp
- Hardware support for LCD landscape/portrait rotation.

Packing List

- IDE cable 1701440500
- FDD cable 1701340600
- Parallel port cable 1701260200
- COM port cable 1701100206
- Audio cable 1700140510
- KB/Mouse cable 1700060192
- USB cable 1709100201
- Jumper cap 9657666600
- Quick Installation Guide
- Utility CD