

Form Factor	PS2 Mini Redundant			
Model Name	EFRP-2402		EFRP-2462	
Input Range	100~240VAC±10%			
Frequency	50/60Hz			
PFC	Active PFC, Power Factor ≥0.95			
DC Output	Max.Load	Min.Load	Max.Load	Min.Load
+3.3V	25A	2A	25A	1A
+5V	25A	2A	25A	1A
+12V	38A	2.5A	43A	2.5A
-12V	0.8A	0.1A	0.8A	0.1A
5VSB	2A	0.1A	2A	0.1A
+3.3V and +5V Combined Power	150W		150W	
Total Combined Power	400W		460W	
Load Regulation	5%			
Line Regulation	1%			
Ripple Noise	1%			
Efficiency	70% at 115V Input			
Hold up Time	18ms			
Protection	OVP/OCP/OTP/SCP			
MTBF	100Khrs, 25°C			
Dimension (mm)	150x86x190			
Operating Temp.	0~50°C		0~40°C	
EMI	Tested According to FCC Class A EN55022/55024 IEC61000-3-2 Class A IEC61000-3-3 EN61000-4-2 EN61000-4-3 EN61000-4-4 EN61000-4-5 EN61000-4-6 EN61000-4-8 EN61000-4-11			
Safety	Designed to meet IEC60950-1 2nd. Edition Certification: UL/TUV/CCC/BSMI			