



Main

Range of product	Modicon Premium Automation platform
Product or component type	Analog output module
Analogue output number	4

Complementary

Analogue output type	Current 0...20 mA Current 4...20 mA Voltage +/- 10 V
Analog/Digital conversion	11_BITS+_SIGN
Conversion time	2.5 ms
Measurement resolution	5.12 mV +/- 10 V 10.25 µA 0...20 mA 10.25 µA 4...20 mA
Electrical connection	Screw terminal block
Measurement error	0.45 % of full scale +/- 10 V 25 °C 0.52 % of full scale 0...20 mA 25 °C 0.52 % of full scale 4...20 mA 25 °C 0.75 % of full scale +/- 10 V 0...60 °C 0.98 % of full scale 0...20 mA 0...60 °C 0.98 % of full scale 4...20 mA 0...60 °C
Isolation between channels	1500 Vrms
Isolation between channels and bus	1500 Vrms
Isolation between channels and ground	500 V
Protection type	Overload protection Short-circuit protection
Output voltage limits	<= 30 V
Load impedance ohmic	< 600 Ohm 0...20 mA < 600 Ohm 4...20 mA > 1000 Ohm +/- 10 V
Load inductance	< 300 µH
Load capacitance	< 0.1 µF
Marking	CE
Current consumption	900 mA 5 V DC
Module format	Standard
Product weight	0.35 kg

Environment

Standards	73/23/EEC 89/336/EEC 92/31/EEC 93/68/EEC CSA 22-2 No 142 CSA 22-2 No 213 Class I Division 2 Group A CSA 22-2 No 213 Class I Division 2 Group B CSA 22-2 No 213 Class I Division 2 Group C CSA 22-2 No 213 Class I Division 2 Group D IEC 61131-2 UL 508
Product certifications	ABS BV DNV (Det Norske Veritas) GL LR RINA RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation for storage 10...95 % without condensation for operation
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2
RoHS EUR conformity date	0843
RoHS EUR status	Compliant