

## CMB-677DC

Mini-ITX Chassis with 80W adapter .



### Overview

COMMELL's CMB-677DC is a Mini-server / terminal platform .the CMB-677DC provides the high reliability solution with high performance and integration. With these features, CMB-677DC should be the advanced solution for you in :

- Industrial Embedded Applied Mini-Server, Transaction Station, POS/POI, KIOSK, ATM, Web Payphone and Terminal Platform
- 3D Video Game Machine, STB (Set-Top-Box), Multi-Media Station and Terminal, Book-size PC, Thin Client, Internet Computer, WebPAD,
- Industrial Panel PC, Portable Workstation, Panel-mount / Wall-mount / Ceil-mount Workstation

### Features

Form Factor	Mini-ITX barebone system
Construction	Heavy-Duty steel
Mini-ITX Board	Inside Motherboard can be : LV-677DC : Intel Core Duo / Core Solo
Drive Bay	External 1 x Slim CD-ROM Space Internal 1 x 2.5" HDD Space
Riser card	No
Thermal Control	One 5 cm system cooling
Front Panel	System Reset switch Power On/Off and HDD activity 2 x USB ports Min-in / Line-out
Rear Side I/O	PS/2 Keyboard and mouse, VGA, DVI ( PCIE-SDVOD add-on card ) , 2 x USB, 1 x RS232 , LPT , 1 x IEEE 1394.  1 x Gigabit LAN, S/PDIF , HDTV/SDTV, Audio, DC input.  2 x PCI space for Mini-PCI card Module.
Environment	Operating Temperature: 0 ~ 50C
Power supply	12V/ 80W adapter
Dimension	208 x 186 x 84 mm
Weight	1.21 kgw , (Without HDD, CD-ROM)