

FEATURES

- > Support for ARINC 429, 419, 453, 561, 568, 573, 575, 582, 708, 717, CSDBand RS-232/422/485 available
- > Up to 64 ARINC channels in one card slot (32 Rx / 32 Tx)
- > Mix different protocols on same board
- > Support for 6-wire ARINC 561 and 568 available
- > Support for RS-232, RS-422, RS-485 available
- > Full and half-length card formats
- > Transition cabling provided
- > Full featured API included for Windows XP, 2000, Me, NT, 98, and 95
- > LabVIEW, LabWindows/CVI, and Visual Basic support are available for ARINC 429, MIL-STD-1553 and selected protocols



The CEI-300 is a flexible, space-saving, multi-protocol solution for PC/AT (ISA bus) computers. Based on rugged and versatile IP module technology (also known as IndustryPack), the CEI-300 provides the proven advantages of open system design while supplying a large number of low cost ARINC 429, ARINC 717 and other interfaces on a single board.

Architecturally, the CEI-300 consists of one or more Condor IP modules, mounted on a 16-bit PC/AT carrier board. The full-length card supports a range of configurations from 2 to 64

ARINC 429 channels. The half-length card supports up to 48 ARINC 429 channels. Multiple cards can be installed in the same PC. For PCI bus support, the CEI-500 is available.

Full featured API support is provided for Windows XP, 2000, Me, NT, 98, 95 and DOS to assist in the integration of the CEI-300 into your system. LabVIEW, LabWindows/ CVI and Visual Basic support are available for ARINC 429. High-level API and GUI support for MIL-STD-1553 is also available on the CEI-300 card.

SPECIFICATIONS

ARINC 429 or 575 Protocols

- Up to 32 Rx / 32 Tx channels
- 12.5, 50 or 100 KHz bit rates

ARINC 561/6, 573 or 717 Protocols

- Up to 4 Rx / 4 Tx channels

Available Interfaces

- ARINC 419, 429, 561, 568, 571, 575, 582, 708, 717, +
- MIL-STD-1553B, CSDB
- RS-232, RS-422, RS-485

Physical

- 4 IP sites on a full board (13.34" x 4.2")
- 3 IP sites on a half board (7.3" x 4.2")

Environmental

- Operating temperature range: 0°C to 70°C

Warranty: 3 year limited hardware warranty

See our on-line Commercial Products Configuration Guide for available configurations.

<http://www.condoreng.com>

