

Ampro ETX 800

Pentium® M Computer-on-Module

Custom, Rugged, Ultra-High Performance



Choose Ampro ETX 800 for...

Rugged, ultra high performance applications that require a custom footprint and connectorization, but with very short time to market and little time for a full custom solution.

Description

Ampro ETX 800 is a small ultra high-performance, low-power Centrino® processor module with advanced networking and high-performance graphics in a modular format that plugs properly into your custom baseboard by offering a choice of FX8 or FX8C connectors per Hirose's requirements.



- Up to 1 GB DDR Memory
- Four USB 2.0 Ports
- 50% Thicker PCB
- Ampro BIOS extensions
- FX8 or FX8C connectors

For more information, pricing, and details on volume discounts, please call us at 1.800.966.5200 or +1.408.360.0200. We'll immediately connect you to your local distributor.

Don't see the product you need? Contact us at 1.800.966.5200 or +1.408.360.0200 for information about our semi-custom and custom solutions.

Get Started Today. Order a QuickStart Kit Now.

Ordering Information

MODEL	DESCRIPTION
ETI-800-K-02	600MHz QuickStart Kit (Q-02 Module, 512MB RAM, Software, Documentation, Ampro ATX Baseboard)
ETI-800-K-10	1.0GHz QuickStart Kit (Q-10 Module, 512MB RAM, Software, Documentation, Ampro ATX Baseboard)
ETI-800-K-22	1.4GHz QuickStart Kit (Q-22 Module, 512MB RAM, Software, Documentation, Ampro ATX Baseboard)
ETI-800-Q-02	600MHz ULV Celeron M CPU
ETI-800-Q-10	1.0GHz ULV Celeron M 373 (Dothan) CPU
ETI-800-Q-22	1.4GHz LV Pentium M CPU

Specifications

PROCESSORS

- Choice of
 - 1.4GHz LowVoltage Pentium® M 738 (Dothan)
 - 1.0GHz Ultra LowVoltage Celeron® M 373 (Dothan)
 - 600MHz Ultra LowVoltage Celeron M
- Cache – 2MB or 512kB Level 2
- Chipset – Intel 855GME/ICH4M
- FSB – 400MHz
- System Controllers – PC-compatible DMA and interrupt controllers and timers
- Real Time Clock – Battery-backed RTC/CMOS
- Watchdog Timer
- Powerfail Reset – Triggers when input voltage drops below predetermined thresholds

MEMORY

- DRAM – Up to 1 GB PC2700 DDR333 SODIMM

BUS INTERFACE

- PCI

I/O

- EIDE – Dual PCI-bus Enhanced Ultra DMA 33/66/100 Synchronous IDE Interface supports up to two hard drives
- Serial – 2 ports, TTL, transceivers on baseboard
- Parallel – EPP/ECP bidirectional port
- Floppy – Supports 1 or 2 drives, shared with parallel
- USB – 4 USB 2.0 ports (four root hubs)
- Keyboard/Mouse – PS/2 interface
- Audio – AC97 speaker; mic, headphone

NETWORK INTERFACE

- Ethernet – Intel 82551ER (10/100 BaseT) Ethernet

VIDEO INTERFACE

- Controller – Integrated Intel Extreme Graphics 2
 - AGP 128-bit 3D engine
 - Supports resolutions to 2048x1536
 - Up to 64MB UMA Frame Buffer
 - Dual channel LVDS flat panel support

SOFTWARE & DEVELOPMENT TOOLS

- OS Support – See Web site for current listings
- BIOS – General Software 5.3 with Ampro extensions

MECHANICAL

- Size – 95x114mm (3.7x4.5"); ETX form factor
- Power Requirements (w/128MB RAM, 100% Loaded)
 - 1.4GHz 3.6A @ 5V
 - 1.0GHz 2.7A @ 5V
 - 600MHz 2.4A @ 5V
- Temperature (100 CFM system air flow)
 - Standard operating: –20° to +70°C
 - Optional operating: –40° to +85°C
 - Storage: –55° to +85°C



AMPRO®

5215 Hellyer Ave., Ste. 110, San Jose, CA 95138 Tel. 408.360.0200 Fax 408.360.0222 sales@ampro.com

NOTICE: The product specifications provided in this data sheet are subject to change without notice. ©2005 Ampro Computers, Inc. All rights reserved. Ampro is a registered trademark and CoreModule, MiniModule, LittleBoard, Little Board, EnCore, ReadyBoard, ReadyBox, ReadySystem and MightyBoard are trademarks of Ampro Computers, Inc. All other trademarks and registered trademarks are the property of their respective owners. DS-ETX800 5K 1205

www.ampro.com