


PMCspan

PMC Expansion Mezzanine



- ◆ Single-slot 6U VMEbus format
- ◆ DEC 21150 PCI-to-PCI interface bridge
- ◆ Support for two single-wide or one double-wide PCI Mezzanine Card (PMC) per PMCspan
- ◆ Stacking capability
- ◆ Front-panel and/or P2 I/O
- ◆ Compliant with PCI local bus specification (revision 2.1)
- ◆ Injector/ejector handles per VME64 extensions
- ◆ Compatible with Motorola's PowerPlus VME series

Provides VMEbus processor modules with greater expansion capabilities

The PMCspan board allows users to customize their exact I/O requirements with Motorola's VME-based CPU modules designed around the PowerPlus architecture.

When a PMCspan board is coupled with an MCG processor module, the system provides up to six PMCs, more expansion capability than any other VMEbus processor module. Each PMCspan board supports either two single-wide or one double-wide PCI Mezzanine Card (PMC). By stacking PMCspan boards onto a processor module, a total of four additional single-wide PMCs can be added to MCG's compute engines—either today or as future application growth demands.

The PMCspan is a standard 6U single-slot VMEbus module that links to its host board via a PCI expansion connector. It supports both front panel and P2 I/O access for customer supplied PMCs.

PMCSpan Details


Carrier Boards

Motorola offers a full line of PowerPC® microprocessor-based VME products which can be custom configured for specific applications via on-board PMC slots. The PMCSpan expands this capability to further increase customizing alternatives. It is compatible with Motorola's PowerPlus VME series. For further information on these host CPUs, contact your local sales representative.

Product Offering

In order to support the increased PCI bus loading associated with additional PMCs, PMCSpan uses the DEC 21150. This PCI-to-PCI interface bridge supports a 32-bit primary bus interface and a 32-bit secondary bus interface. PMCSpan mates directly with the host CPU via the separate PCI expansion connector.

When the maximum of two PMCSpan modules are stacked together, the top board does not require a second PCI-to-PCI interface bridge. Software views this secondary module as an extension to the primary PMCSpan.



The flexible design of the PMCSpan can be quickly and easily customized for a variety of industry-specific applications.

Specifications

Form Factor

Single-slot 6U VMEbus format

PCI-to-PCI Interface

Controller: DEC 21150 PCI-to-PCI interface bridge

Address/Data: A32/D32

PCI Bus Clock: 33 MHz

Signaling: 5V

Mating Connector on Host Board: 114-pin PCI Expansion Connector; still allows use of host CPU's original PMCs

Compliance: PCI Local Bus Specification, Revision 2.1

IEEE P1386.1 PCI Mezzanine Card Slots

Address/Data: A32/D32, PMC PN1, PN2, PN4 connectors

PCI Bus Clock: 33 MHz

Signaling: 5V

Power: +3.3V, +5V, ±12V, 7.5 watts max. per PMC

Module Types: Two single-wide or one double-wide, front-panel or P2 I/O

P2 PMC I/O: 64 I/O signals from first PMC routed to VMEbus P2 connector

Power Requirements (no PMCs installed)

Power: +5V @ 0.44 ampere (max.)

+12V @ 0 ampere (max.)

-12V @ 0 ampere (max.)

Board Size

Height: 233.4 mm (9.2 in.)

Depth: 160.0 mm (6.3 in.)

Front Panel Height: 261.8 mm (10.3 in.)

Width: 19.8 mm (0.8 in.)

Demonstrated MTBF

(based on a sample of eight boards in accelerated stress environment)

Mean: 190,509 hours

95% Confidence: 107,681 hours

Environmental

	Operating	Nonoperating
Temperature:	0° C to +55° C, forced air cooling	-40° C to +85° C
Altitude:	5,000 m	15,000 m
Humidity (NC):	10% to 80%	10% to 90%
Vibration:	2 Gs RMS, 20-2000 Hz random	6 Gs RMS, 20-2000 Hz random

Electromagnetic Compatibility (EMC)

Intended for use in systems meeting the following regulations:

U.S.: FCC Part 15, Subpart B, Class B

Canada: ICES-003, Class B

This product was tested in a representative system to the following standards:

CE Mark per European EMC Directive 89/336/EEC with Amendments; Emissions: EN55022 Class B; Immunity: EN50082-1

Safety

All printed wiring boards (PWBs) are manufactured with a flammability rating of 94V-0 by UL recognized manufacturers.

Ordering Information

PMCSpan-001:	Primary PCI expansion provides two PMC modules for the MVME2600, MVME3600, or MVME4600, includes DEC 21150, optional PMCSpan-010, IEEE 1101 compatible front panel with injector/ejector handles
PMCSpan-002:	Same as PMCSpan-001 but mates only with the MVME2300/2400
PMCSpan-010:	Secondary PCI expansion provides two additional PMC modules, does not include DEC 21150, requires PMCSpan-00x
PMCSpan1-001:	PMCSpan-001 with original VME Scanbe front panel and handles
PMCSpan1-002:	PMCSpan-002 with original VME Scanbe front panel and handles
PMCSpan1-010:	PMCSpan-010 with original VME Scanbe front panel and handles
Documentation	
PMCSpanA/IH:	PMC Carrier Installation and Use Manual
Documentation is available for on-line viewing and ordering at http://www.motorola.com/computer/literature .	



MOTOROLA

www.motorola.com/computer
1-800-759-1107

Motorola Computer Group
2900 S. Diablo Way
Tempe, AZ 85282

Regional Sales Offices

Canada & Central Pan America

400 Matheson Blvd. West
Mississauga, Ontario
L5R 3M1 Canada
905-507-7135 or 888-366-3624

Eastern Pan America

1650 Tysons Boulevard, Suite 250
McLean, VA 22102
703-714-0725

Western Pan America

1150 Kifer Road, Suite 202
Sunnyvale, CA 94086
408-991-8633

Asia Pacific and Japan

34/F Nat West Tower
Times Square, 1 Matheson St
Causeway Bay, Hong Kong
852-2966-3209

East Mediterranean

6 HaTaas Street
Ramat-Gan, Isreal 52523
972-3-610-4388

France

Zone Technopolis - Immeuble
THETA 3, avenue du Canada - BP304
91958 LES ULLIS
Courtaboeuf Cedex, France
+33 (0) 1 64 86 64 00

Germany

Hagenauer Strasse 47
D-65203 Wiesbaden, Germany
+49 (0) 611-3611 604

Benelux

De Waal 26, 5684 PH Best
PO Box 350, 5680 AJ Best
Netherlands
+31 4993 61250

Nordic

Dalvagen 2
S-169 56 Solna, Sweden
+46 (0) 8 734 8800

United Kingdom

London Road, Old Basing,
Basingstoke, Hampshire
RG24 7JL England
+44 (0) 1256 790555

Motorola and the Motorola logo are registered trademarks and The Heart of Smart, DigitalDNA and the DigitalDNA logo are trademarks of Motorola, Inc. PowerPC and the PowerPC logo are registered trademarks of International Business Machines Corporation and are used by Motorola, Inc., under license from International Business Machines Corporation. All other names, products, and services mentioned are trademarks or registered trademarks of their respective holders.

This data sheet identifies products, their specifications, and their characteristics, which may be suitable for certain applications. It does not constitute an offer to sell or a commitment of present or future availability, and should not be relied upon to state the terms and conditions, including warranties and disclaimers thereof, on which Motorola may sell products. A prospective buyer should exercise its own independent judgement to confirm the suitability of the products for particular applications. Motorola reserves the right to make changes, without notice, to any products or information herein which will, in its sole discretion, improve reliability, function, or design. Motorola does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent or other intellectual property rights or under others. This disclaimer extends to any prospective buyer, and it includes Motorola's licensee, licensee's transferees, and licensee's customers and users. Availability of some of the products and services described herein may be restricted in some locations.

Copyright 1997 Motorola Inc. PMCSpan-D2 5/00