

Product Specifications

VAMP-SlimVista

Flat Panel Monitor Family Offers Agency Approvals



The SlimVista family consists of ultra-thin flat panel monitors featuring durable plastic enclosures that can be used on the desktop, wall or swing arm mounted.

19" Display Specifications

- Display 19.0" 1280x1024 16.7M color TFT LCD; 250 nit; 500:1 contrast ratio
- Viewing angle +/-85° X and Y axis

19" System Specifications

- Dimensions 20.1" x 19.7" x 8.27" (WxHxD)
510 mm x 500 mm x 210 mm
- Front controls Power, Menu, Select, Adjustment (+,-)
- OSD Auto-configuration; Brightness; Contrast; Clock; Phase; H-, V- and OSD-position
- Plug & Play DDC2B compatible
- Power 55W; VESA DPMS compatible
- Power supply 100 - 240 VAC, 50 - 60 Hz input
- Scanning freq. Horizontal sync.: 31.5 KHz to 80 KHz
Vertical sync.: 56 Hz to 75 Hz
1280x1024 @ 75 Hz
- System weight 26.5 lbs (12 kg)
- Temperature 0° - 50°C (operating)
-20° - 65°C (storage)
- Humidity 10 - 80% (no condensation)
- Certification UL, CSA, TUV/GS, CE, FCC-B, MPR II, TCO'99 (optional)

19" Options

- Touchscreen Resistive

19" Ordering Information

VAMP-SlimVista-19

17" Display Specifications

- Display 17.1" 1280x1024 16.7M color AMTFT; 250 nit; 350:1 contrast ratio
- Viewing angle +/-80° X axis; -80° to 55° Y axis

17" System Specifications

- Dimensions 16.9" x 17.5" x 8.1" (WxHxD)
429 mm x 445 mm x 206 mm
- Front controls Power on/off with LED, Menu, Select, Adjustment (+,-), P-I-P, Zoom-in/Zoom-out
- OSD Brightness, Contrast, Clock, Phase, Auto-tune, H-position, V-position, RGB color drive, OSD format, Volume
- Speaker Internal 2W/per channel driver
- Power Embedded power system, universal 90 - 264 VAC input
- Temperature 0° - 50°C (operating)
-20° - 65°C (storage)
- Humidity 10 - 80% non-condensing

17" Options

- Touchscreen Resistive, capacitive, SAW
- Mounting Adjustable arm

17" Ordering Information

VAMP-SlimVista-17-Options

15" Display Specifications

- Display 15" 1024x768 16.7M color AMTFT LCD
- Brightness 250 nit
- Touchscreen Resistive; utilizes RS-232 controller
- Power supply External 100 - 240 VAC, 50 - 60 Hz
- Mounting Tabletop stand; 75 mm VESA with tabletop stand removed

15" Options

- Color Beige or black
- Audio One watt per channel
- Dimensions 16" x 15.5" x 5" (WxHxD)
406 mm x 394 mm x 127 mm
- System weight 5.3 kg, 11.66 lbs.

15" Ordering Information

SlimVista-Bk

SlimVista-Bg

Specifications may change without notice due to component changes.



VMIC | RAMiX | Computer DYNAMICS

GE Fanuc Embedded Systems Information Center — Greenville Location

Computer Dynamics, 7640 Pelham Road, Greenville, SC 29615

Phone: (864) 627-8800 • Fax: (864) 675-0106 • www.gefanuc.com/ipc

© 2004 GE Fanuc Automation Americas, Inc. All rights reserved. All other brands or names are the property of their respective holders. Specifications are subject to change without notice. Reproduction or copying of images is prohibited without the express written permission of GE Fanuc Embedded Systems, Inc. 10/04