


➤ 889LCD/ATX

Intel® Pentium® 4 & Intel® Celeron®
Industrial ATX Motherboard, lead free
GbE LAN, FSB800, S-ATA, PCI Express®



PCI EXPRESS™



Intel®
Communications
Alliance
Premier Member
GOLD

- ATX Long-term supply Industrial Motherboard
- Intel® Pentium® 4 & Celeron® Processors (LGA775)
- Lead-free production
- Support for Hyper-Threading Technology
- Front Side Bus 800/533 MHz
- Intel® 915G + ICH6 Chipset
- Up to 4 GByte of DDR2 533/400 SDRAM
- 1x PCI Express® x16, 2x PCI Express® x1, 4x PCI
- Intel® GMA900 Graphics Controller
- Flat Panel Display Support via ADD2-Card
- 1x GBit Ethernet LAN, 1x RS232C, 8x USB 2.0


► Technical Data

Processor	Intel® Pentium® 4 & Intel® Celeron® (LGA755) Support for Hyper-Threading Technology 3.x+ GHz
Chipset	Intel® 915G and Intel® ICH6 Chipset
Front Side Bus	800/533 MHz
BIOS	Phoenix®
Power Management	ACPI and APM
Bus	1x PCI Express x1, 4x PCI (32Bit/33MHz)
PEG/SVDO	1x PCI Express x16 /SVDO for ADD2 Card
SDRAM	Up to 4 GByte of DDR400 SDRAM (PC 3200), 4x DIMM Sockets, no ECC
Graphics	Intel® GMA 900 Graphics Controller 2D/3D Graphics Engine, HW assisted DVD/MPEG2 Decoding
Resolution	Up to 2048 x 1536
Display	Onboard CRT External High End Graphics Card via PCI Express x16 Interface LVDS/DVI Digital Displays via ADD2-Cards (option)
HDD	4x SATA150, 1x ATA100, 1x FDD

Parallel Port	Bi-directional Centronics w. ECP or EPP Mode
Serial Port	1x RS232C NS16C550 Serial Ports with FIFO
USB	8x USB 2.0, 4x internal and 4x external
Ethernet	1x Gbe LAN (10/100/1000)
Keyboard/Mouse	Standard PS/2 Keyboard and Standard PS/2 Mouse
Audio	Audio Mic in, Line in and Line out
Monitoring	Temperature, Fan and Voltages
Battery	On board Lithium
Monitoring API	Software interface to monitor hardware values including HDD S.M.A.R.T.
Battery	On board Lithium
Power Supply	ATX 12V (20 Pin) or BTX (24 Pin)
Operating Temp.	0 - 50°C
Dimensions	ATX, 304.8mm x 243.8mm (12" x 9.6")
Environmental	Lead free, Hologene free

► Ordering Information

Article	Part.-No.	Description
886LCD/ATXU	710040-1000	Socket LGA775, Intel® 915G, w. 1x PCIe, 2x PCI



ADD2-DVI

► Corporate Offices

Kontron AG
Oskar-von-Miller-Straße 1
85386 Eching/Munich
Germany

Tel.: +49 (0)8165/ 77 0
Fax: +49 (0)8165/ 77 219
sales@kontron.com

Kontron America
14118 Stowe Dr
Poway, CA 92064-7147
USA

Tel.: +1 888 294 4558
Fax: +1 858 677 0898
sales@us.kontron.com

Asia Pacific
4F, No. 415, Ti-Ding Blvd.
Sec. 2, NeiHu District
Taipei, Taiwan 114

Tel.: +886-2-2799-2789
Fax: +886-2-2799-7399
sales@kontron.com.tw

Kontron Technology A/S
Dr. Neergaards Vej 5D
2970 Hørsholm
Denmark

Tel.: +45 4576 1016
Fax: +45 4576 1017
motherboard@kontron.com