

Industrial Single Board Computer

Ultra Compact Mini-FlexATX Motherboard



LV-670

Mini-FlexATX Socket 478 DDR Motherboard
Ultra Compact @ 170 x 170 mm of Dimension
with Intel 845GV/ICH4 Chipset, 533/400 MHz FSB
Intel Extreme Graphics, LAN, Audio, SPDIF, TV-out
Hi-Speed USB 2.0, IEEE 1394 Interfaces



Form Factor	Mini-FlexATX (Mini-ITX), 170 x 170 mm (W x L)
CPU	Socket 478 Intel Pentium 4 / Celeron CPU @ 533/400 MHz FSB Intel 0.13-micron Northwood, 0.18-micron Willamette CPU supported
Memory	One 184-pin DIMM socket supports up to 1 GB DDR200/266/333 SDRAM
Chipset	Intel 845GV and ICH4
Watchdog Timer	Generates NMI or system reset with 1 to 255 sec./ min. of time out value
Power Management	ACPI 1.0 compliant, supports power saving mode with ATX power supply
Expansive Interface	1 x PCI slot supports up to 2 x PCI bus master of add-on cards with riser card
PCI Enhanced IDE	Dual UltraATA/100 bus master IDE channels up to 4 ATAPI devices One 40-pin IDE1 and one 44-pin IDE2 interfaces
VGA Interface	Intel 845GV series chipset built Intel Extreme Graphics with 266 MHz VGA core, 256-bit 3D engine and dynamic video memory up to 64 MBytes
TV-out Interface	Chrontel CH7011 TV-out encoder with AV and S-video output
LAN Interface	Intel PRO/100+ LAN with Intel ICH4 and 82562ET phy
Hi-Speed USB 2.0	Intel ICH4 built-in Hi-Speed USB 2.0 interface with up to 480 Mbps of data transfer rate
IEEE 1394	Agere FW323 IEEE 1394 controller with 100/200/400 Mbps of data transfer rate
Audio Interface	AC97 3D audio interface with line-in, line-out, Mic-in, CD-in and SPDIF interface
Multi-I/O Port	1 x COM, 1 x parallel, 4 USB 2.0, 1 x IrDA, 1 x FDD, 1 x PS/2 keyboard and mouse port
External I/O Panel	PS/2 keyboard and mouse port AV/S-video TV-out, VGA, LPT port Dual USB 2.0, LAN port IEEE 1394, Audio line-in, line-out, mic-in, SPDIF
Solid State Disk	DiskOnModule IDE-based, bootable, driver free flash disk with up to 256 MB of capacity M-systems DiskOnChip IDE Pro with TrueFFS and ECC/EDC data protection
Environment	Power Requirement: ATX power connector Board Dimension (W x L): 170 x 170 mm. Standard Mini-FlexATX form Factor Operation Temperature: 0 ~ 60°C (32 ~ 140°F)
Ordering Code	LV-670 Mini-FlexATX Socket 478 Pentium 4 DDR Motherboard with Intel 845GV/ICH4 Chipset, 400/533 MHz FSB, DDR266/333 SDRAM Intel VGA, LAN, Audio, SPDIF, Hi-Speed USB 2.0, IEEE 1394, TV-out

Online product information detail and updates are available at: <http://www.commell.com.tw>

COMMELL IPC Division, Taiwan Commate Computer Inc.

8F, No. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan
TEL : +886-2-26963909 Website: <http://www.commell.com.tw>
FAX : +886-2-26963911 E-mail : info@commell.com.tw

COMMELL
www.commell.com.tw