

CSB100-550 NEW

Fanless



Features

- Onboard AMD Geode™ LX800 processor, 500MHz
- Fanless slim box design for a wide variety of applications
- One 2.5" 160GB SATA HDD
- Chassis available in black color
- Wall mount kit included

Specifications

System Mainboard	IB550F
CPU Type	AMD Geode™ LX800
System Speed	500MHz
Memory	1x DDR2 SO-DIMM
Construction	SECC
Chassis Color	Black
Front Panel External I/O	Front audio, Power switch
Rear Panel External I/O	2x USB ports, 1x VGA connector, 1x COM ports, 1x RJ-45 connector, KB/MS connector, DC-in Jack
Storage	1x 2.5" 160GB HDD
Power Supply	60W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	172.4mm(W) x 125mm(D) x 52.4mm(H)

Environmental

Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

CSB100-550	Steel Chassis with IB550F 3.5" SBC, 2.5" 160GB SATA HDD, 60W power adaptor
------------	--



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.