

# ➤ VL203 886 LCD/ATXU (GV)



Small Depth

Small Price

Small TCO



## Protecting your investment

- Excellent performance size ratio
- P4 inside
- Ensures scalability with 3 free PCI half-size slots
- Scalable power for Space Limited Applications

## ➤ Product Overview

The VL203 2U system, with its small unit depth and compact size, is ideal for space limited environments typically found in industrial communications and fieldbus applications.

The three PCI expansion slots along with its built in reliability ensure system longevity and scalability.

In ever changing industrial application environment, system requirements will evolve and grow. The VL203 solutions simplified features not only facilitate system control and data acquisition, but also enable fast and easy configuration and upgradeability to meet new requirements as they develop.

## ➤ Technical Information

<b>System</b>	
VL 203 886 LCD/ATXU (GV)	
<b>Product Line</b>	
VL 203	
<b>Dimension (H x W x D)</b>	
Desktop Version	Rackmount Version
88 mm x 441 mm x 450 mm	88 mm x 482 mm x 450 mm
3,5" x 17,4" x 17,7"	3,5" x 19" x 17,7"
<b>Weight</b>	
Approx. 10 kg	
<b>Interfaces Front</b>	
2 x USB 2.0	
<b>Interfaces of the installed board (rear)</b>	
1 x LAN 10/100, 1 x RS232, 1 x VGA, Audio AC97, 1 x LPT, PS/2 Mouse + Keyboard, 4 x USB 2.0	
<b>Controls on the frontside</b>	
ATX Switch, Reset	
<b>External accessible drive bays</b>	
1 x 5,25", 1 x 3,5"	
<b>Internal drive bays</b>	
2 x 3,5"	
<b>Power supply</b>	
115/230 V, 300 W (PFC)	
<b>Expansion slots</b>	
3 x PCI 32 Bit	
<b>Memory</b>	
Up to 2 GB DDR SD RAM	

<b>Processor</b>	
Pentium 4: Celeron 2,0 GHz, P4 2,4 GHz, P4 2,8 GHz Pentium M: Celeron 1,3 GHz, PM 1,6 GHz, PM 1,8 GHz	
<b>Temperature</b>	
0°C - +45°C operating	
<b>Humidity</b>	
10-90 % non operating 20-90 % operating	
<b>Shock</b>	
basic industrial grade	
<b>Vibration</b>	
basic industrial grade	
<b>Approvals</b>	
CE	
<b>MTBF</b>	
25.000 h	
<b>Protection Class</b>	
Front IP20	
<b>Options</b>	
Side Rails	



## ➤ Corporate Offices

EMEA  
Kontron AG  
Oskar-von-Miller-Straße 1  
85386 Eching

Tel: +49 (0)8165/77 0  
Fax: +49 (0)8165/77 219  
sales@kontron.com

NORTH AMERICA  
Kontron America Corporate Office  
14118 Stowe Drive  
Poway CA, 92064-7147

Tel.: (888) 294-4558  
Fax: (858) 677-0898  
sales@kontron.com

Asia Pacific  
4F, No. 415, Ti-Ding Blvd.  
Sec. 2, NeiHu District  
Taipei, Taiwan 114

Tel: +886 2 2799 2789  
Fax: +886 2 2799 7399  
sales@kontron.com.tw