

# Product Specifications



PMGS3-2U

Material ID: 760001669

GigaSPEED® XL PATCHMAX® GS3 Category 6 U/UTP 2U Panel Kit



## CHARACTERISTICS

### Dimensions

Depth	206.50 mm   8.13 in
Height	89.66 mm   3.53 in
Width	482.60 mm   19.00 in

### Electrical Specifications

ANSI/TIA Category	6
-------------------	---

### Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	UL/cUL listed
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

### General Specifications

Product Type	Panel
Color	Black
Package, quantity	1
Rack Type	EIA 19 in
Rack Units	2

### Mechanical Specifications

Material Type	High-impact, flame retardant, thermoplastic   Powder-coated steel
---------------	---

### Regulatory Compliance/Certifications

**Agency**  
RoHS 2002/95/EC  
ISO 9001:2000

**Classification**  
Compliant  
Compliant



**SYSTIMAX®**  
SOLUTIONS  
www.commscope.com

©2009 CommScope, Inc. All rights reserved.  
All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope.  
All specifications are subject to change. See www.commscope.com for the most current information.