



Andrew Solutions
204679A-14

Boot Assembly, 4 in, for 5/8 in corrugated coaxial cable

OBSOLETE

Replaced By:

SEC-358

SnapSeal™ Entry Cushion with 3 holes for 5/8 in corrugated coaxial cable

Dimensions

| | |
|--------------|---------------------|
| Nominal Size | 5/8 in |
| Height | 101.60 mm 4.00 in |
| Length | 76.20 mm 3.00 in |

General Specifications

| | |
|--------------------|-----------------------------|
| Cable Type | Corrugated |
| Cables per Cushion | 3 |
| Color | Black |
| Includes | Boot Cushion Two clamps |
| Material Type | EPDM rubber |
| Package Quantity | 1 |

Mechanical Specifications

| | |
|--------------------------------------------|----------------------------------------|
| UV Resistance Test Method | MIL-STD-810E, Procedure 11, Method 505 |
| UV Resistance, minimum with no degradation | ≥1000 hours |
| Weather Resistance Test Method | 04AS00-03.9.0 IEC 60529:2001, IP66 |

Packed Dimensions

| | |
|-----------------|-------------------|
| Height | 149.9 mm 5.9 in |
| Length | 79.8 mm 3.1 in |
| Shipping Weight | 0.64 kg 1.42 lb |
| Width | 149.9 mm 5.9 in |

Regulatory Compliance/Certifications

Agency

RoHS 2002/95/EC
China RoHS SJ/T 11364-2006

Classification

Compliant
Below Maximum Concentration Value (MCV)

