

Intel® PRO/1000 MT Server Adapter

High-Performance Gigabit Copper Connection for Servers

The Intelligent Way to Connect

Eliminate server bottlenecks and migrate existing Category-5 networks to Gigabit Ethernet easily and cost-effectively with the Intel® PRO/1000 MT Server Adapter. Featuring flexible, auto-negotiating 10/100/1000 Mbps performance, the Intel PRO/1000 MT Server Adapter is designed to automatically scale with growing networks.

Enhance server performance further by teaming multiple
Intel® PRO Server Adapters using Intel® expanded advanced server
feature software to achieve multi-Gigabit scalability and redundant
failover capability. With a flexible design that fits almost any type of PCI
bus, the standards-based management features and wide network operating system
support help to ensure extensive compatibility with the latest server and networking environments.

Features	Benefits	
WIDESPREAD COMPATIBILITY		
Support for most NOSs	Enables widespread deployment	
Intel [®] SingleDriver™ technology	Common driver suite for Gigabit Ethernet reduces installation complexity	
Backward Compatibility with previous generations of Intel PRO/1000 Network Adapters	Reduces support costs and simplifies installation and maintenance	
Supports 64- or 32-bit PCI-X 1.0 or PCI 2.2 buses	This flexible and auto-sensing adapter works in a variety of bus types	
Remote Management Support (WfM, RIS, SNMP/DMI)	Reduces support costs with remote management based on industry-wide standards	
IEEE 802.3ab Compatibility	Supports industry-wide Gigabit Ethernet networking standar	
NEW FEATURES IN THE INTEL PRO/1000 MT SERVER ADA	APTER	
Intel® 82545 Gigabit Controller	Provides high performance, reliability, and low power use in a single integrated Gigabit Ethernet controller chip	
Full-height and low-profile, screw-on brackets included with each adapter	Compatible with full-height and low-profile PCI slots—the standard, full-height bracket can be easily swapped out and replaced by the shorter, low-profile bracket, for installation in high-density 1U and 2U servers that feature low-profile PCI slot	
Interrupt Moderation	Delivers increased performance while significantly reducing CPU utilization	
Advanced Cable Diagnostics	Dynamically tests and reports network problems (error rate, cable length) and automatically compensates for cable issue (cross over cable, wrong pin-out/polarity)	
Large Send Off-load/TCP Segmentation Off-load	Compatible with Large Send Off-load feature of Microsoft Windows* Server 2003, 2000 and XP which enables wire spee performance with low CPU utilization	
Expanded Advanced Server Features	Intel® ANS software increases uptime with redundant, teamed connections and scales bandwidth by balancing network trafficacross multiple server connections. Now offers Switch Fault Tolerance and Test Switch Configuration to test compatibility and further increase uptime	

- Easy, cost-effective 10/100/1000 migration over CAT-5 cabling
- Multi-Gigabit scalability and increased uptime through advanced server features
- Optional low-profile bracket included for high-density, rackmounted servers



Gigabit speeds on Category-5 cable networks Able to achieve Gigabit speeds on commonly deployed CAT-5 cabling without costly cable replacement Compatible with Fast Ethernet Reduces training costs and ramp rollout quickly Auto-sensing, self-configuring 10/100/1000 Mbps performance Enables migration to faster networks easily and inexpensively—adapter will automatically sense when the network is able to support a faster speed, and self-configure to save IT staff time, money and server downtime

SPECIFICATIONS		Intel® PRO/1000 MT Server Adapter		
GENERAL Product Codes Connectors IEEE Standard/Network Topology Wiring ADAPTER PRODUCT FEATURES Intel® SingleDriver™ technology Plug and Play Specification Support Easy Installation, Intel® PROSet Utility and Intel® PRO Intelligent Install	PWLA8490MT RJ-45 10BASE-T, 100BASE-TX, 1000BASE-T Cat-5, 4-pair	ADVANCED SOFTWARE FEATURES Adapter Fault Tolerance Switch Fault Tolerance Adaptive Load Balancing Fast EtherChannel* Gigabit EtherChannel* IEEE 802.3ad (Link Aggregation Control Protocol)* Test Switch Configuration PCI Hot Plug* and Active PCI* 802.1Q VLANs 802.3x Flow Control		
Auto-negotiation, Full-duplex Capable Includes a Low-profile and a Full-height Bracket Cable Distance NETWORK MANAGEMENT Wired for Management (WfM) Baseline v2.0	100m	TCP Checksum Offload IEEE 802.1p TCP Segmentation/Large Send Off-load Interrupt Moderation Save and Restore		
Enabled for Servers DMI 2.0 Support, WMI & SNMP-manageable Offline Diagnostics Dynamic Cable Diagnostics Intel® Boot Agent ACPI Power Management PXE 2.0		TECHNICAL FEATURES Data Rate(s) Supported per Port Bus Type Bus Width Bus Speed (MHz) Onboard Memory Interrupt Levels	10, 100 & 1,000 Mbps PCI/PCI-X 32- or 64-bit 33/66/100/133 64 KB INTA	
NOS SOFTWARE SUPPORT Microsoft Windows* Server 2003 and 2000 Microsoft Windows* XP 32- and 64-bit Editions Microsoft Windows NT* 4.0 Linux* 2.4.x or later (32- and 64-bit) FreeBSD 4.x or later Novell Netware* 4.11, 4.2, 5.0, 5.1, 6.0		IEEE Support Hardware Certifications Data Transfer Mode Controller—Processor Typical Power Consumption Operating Temperature Operating Humidity	802.3ab FCC A, CE Bus-master DMA Intel® 82545 1A at +5VDC 0-55°C 85% at +55°C	
SunSoft Solaris* 7, 8 UnixWare* 7.x, OpenUNIX 8 (ddi8) SCO5* INTEL BACKING Limited Lifetime Warranty 90-day Money-back Guarantee (U.S. and Canada)	:	PHYSICAL DIMENSIONS Length Width Height of Full-Height End Bracket Height of Low-Profile End Bracket	16.5cm (6.6 in) 6.4cm (2.5 in) 12.1cm (4.75 in) 8.1cm (3.2 in)	

ORDER CODES

PWLA8490MT (Single Packs)
PWLA8490MTBLK5 (Five Packs)

COMPANION PRODUCTS

Consider these Intel® products in your sever and network planning:

- Intel® PRO/1000 MT Desktop Adapters
- Intel® PRO/1000 MF Server Adapters
- Intel® PRO/1000 MF Server Adapters (LX)
- Intel® PRO/1000 MF Dual Port Server Adapters
- Intel® PRO/1000 MT Dual Port Server Adapters
 Intel® PRO/1000 MT Quad Port Server Adapters
- Other Intel® PRO Desktop, Mobile, Wireless and Server Adapters
- Intel® Xeon™ processors
- Intel® Server Boards

NETWORK-READY PCS

Top PC and server manufacturers offer Intel® adapters in their new products. Specify or ask for Intel® PRO Network Connections with your next PC, server, or mobile PC purchase. For a list of preferred suppliers, visit us on the World Wide Web: www.intel.com/network/connectivity/how_to_buy/index.htm.

CUSTOMER SUPPORT

Intel® customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at support.intel.com/support/network. Service and availability may vary by country.

FOR PRODUCT INFORMATION

To speak to a customer service representative regarding Intel® products, please call 1-800-538-3373 (U.S. and Canada) or visit www.intel.com/support/9089.htm for the telephone number in your area. For additional product information on the Intel® Networking and Communication products, visit www.intel.com/network/connectivity.

ONLINE DOCUMENTS

For the latest product information, visit us on the World Wide Web at www.intel.com/network/connectivity.



Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life-saving, or life-sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit http://www.intel.com/network/connectivity

*Other names and brands may be claimed as the property of others.

¹Available only when used with a capable switch.

Copyright © Intel Corporation 2003. All rights reserved. 1003/LAD/PL/OC/PDF

