# NPort 1220, 1220I

# Isolated 2-Port RS-422/485 USB-to-Serial Hub

# **Features**

- Expand to 2 RS-422/485 ports via USB
- Supports 4-wire RS-422/485 and 2-wire RS-485 applications
- Hot plug and play
- Supports bus power and external power
- No additional I/O, IRQ required
- RS-422/485 speed up to 115.2 Kbps
- Supports USB 1.1, full rate speed up to 12 Mbps
- Built-in 16 KV ESD Surge Protection
- Supports 2 KV Isolation (NPort 1220I)





## Instant Plug and Play


NPort 1220 gives your laptop or workstation the ability to communicate between a USB (Universal Serial Bus) port and up to 2 RS-422/485 serial peripherals. NPort 1220 adds 2

Windows serial COM ports via its USB port, and is compatible with new and legacy RS-422/485 devices.

# Simplified, Hassle-Free Serial Port Expansion

USB plug and play allows easy serial port expansion and requires no IRQ, DMA, or I/O port resources. Users no longer

need to open the chassis or power down the system, saving on setup time and cost.



### Total Solution for Industrial Device Networking

## **Dimensions**



## **Specifications**

#### USB

Compliant with USB 1.1, 1.0 USB 2.0 backwards compatible Connector: USB type B Speed: 12 Mbps at full speed Serial No. of Ports: 2 Interface: 4-wire RS-422: TxD+/-, RxD+/-, GND 4-wire RS-485: TxD+/-, RxD+/-, GND 2-wire RS-485: Data+/-, GND **Connector:** Terminal Block FIFO: 128 bytes Serial line protection: 16 KV ESD for all signals **Serial Communication Parameters** Parity: None, Even, Odd Data bits: 7,8 Stop bit: 1, 2

RS-485 Data Direction Control: Patented ADDC<sup>™</sup> (Automatic Data Direction Control (ADDC<sup>™</sup>)

#### Power Requirements

Power Input: 12 to 48 VDC (external) or 5 VDC (Bus power) Power Consumption: BUS: 140 mA @ 5 VDC Ext. PWR: 306 mA @ 12 VDC

#### **Mechanical Specifications**

Material: ABS Gross Weight: 220±5g (0. 48 lb) Environmental Operating Temperature: 0 to 55°C (32 to 131°F) Storage Temperature: -20 to 75°C (-4 to 167°F) Operating Humidity: 5 to 95% RH Regulatory Approvals

#### EMC: FCC (Class B), CE

Safety: UL, CUL, TÜV Warranty: 5 years

## Odering Information

Speed: 600 to 115.2 Kbps

NPort 1220: USB to 2-Port RS-422/485 Serial HUB NPort 1220I: USB to 2-Port RS-422/485 Serial HUB with Isolation

#### All Items Include:

- 1 USB-to-Serial HUB
- Quick Installation Guide

• Documentation and Software CD-ROM

#### **Optional Accessories:**

• DIN-Rail Mounting Kit (35 mm)