



## Power Supply

(Catalog No. 2707-PS120)

### Instructions

#### Description

The Power Supply (Catalog Number 2707-PS120) can be used with the following:

- MicroView Hand-Held Operator Interface (Catalog Number 2707-MVH232)
- MicroView Panel-Mount Operator Interface (Catalog Number 2707-MVP232)

#### Power Supply Installation



**ATTENTION:**

The Power Supply (Catalog No. 2707-PS120) has the following polarity:



If using another power supply, the polarity must be the same.

1. Plug the circular connector of the power supply into the receptacle on the unit.
2. Plug the power supply into a standard AC power source.

#### Power Supply Specifications

**Electrical:**

Input Voltage 120V AC±10%, 60Hz  
Rated Output 18V DC @ 100mA typical unregulated  
Short circuit protection  
Thermal protection

**Physical:**

Dimensions 2.40" (H) x 2.17" (W) x 1.59" (D)  
[61 mm (H) x 55 mm (W) x 41 mm (H)]  
Weight 8.11 ounces (230 grams)  
Cable Length 6 feet (2.36 m)

**Environmental:**

Operating Temperature 0°C to 40°C (32°F to 104°F)  
Storage Temperature -10°C to 70°C (14°F to 158°F)  
Relative Humidity 10% to 90% (without condensation)  
Certification UL Listed

 **Rockwell** Automation

---

**Allen-Bradley**