

# 30 WATT AC-DC CONVERTER ERT-FWA SERIES

Specifications<AC/DC>	Model					
	ERT**FWA 30WATTS/2OUTPUTS		ERT21FWA-B	ERT22FWA-B	ERT24FWA-B	
<b>Input Characteristic</b>						
Input Voltage	AC 100V(DC 130V)					
Input Range	AC 85-132V(DC 110-170V)					
Input Frequency	50/60Hz					
Input Frequency Range	47-440Hz					
Phase	Single					
Inrush Current *1	30A(maximum) at AC 100V					
Efficiency [%] (typical) *2	73		71		70	
<b>Output Characteristic</b>						
Output Voltage [V]	24	5	12	12	12	5
Output Current [A]	0.2-1.0(Peak1.5)	1.5	0.4-2.0(Peak2.7)	0.8	0.2-2.0(Peak2.7)	1.5
Voltage Adjust Range	V1:+3%/-0% of Rated Output Voltage(at no load within the input range) V2:fixed with tolerance of +/-3.5% (at no load within the input range)					
Ripple and Noise [mVp-p](maximum) *3	290	100	170	170	170	100
<b>Regulation</b>						
a.Statistic Line Regulation [mV](maximum)	120	25	60	60	60	25
b.Statistic Load Regulation [mV](maximum)	240	50	120	120	120	50
c.Temperature Coefficient *4	0.03%/°C					
d.Drift[mV](maximum) *5	135	40	75	75	75	40
e.Dynamic Load Regulation [mV](typical) *6	not specified					
f.Recovery Time *6	not specified					
Rise up time	200mS(maximum) at 25°C and rated input/output					
Hold up time	20mS(minimum) at 25°C and rated input/output					
<b>Functions</b>						
Overcurrent Protection Current[A]	≥ 105% of Rated Output	V1:Current Limiting with automatic recovery V2:by the regulator I.C's characteristics				
Overvoltage Protection Voltage[V]	≥ 115% of Rated Output	≥ Peak	-	≥ Peak	-	≥ Peak
Remote Sense	not available					
Remote On/Off	not available					
<b>Environmental</b>						
Operating Temperature	-5 to +50°C [enclosed type:-5 to 50°C at vertical mount/-5 to 40°C at horizontal mount]					
Operating Humidity	85% RH(non-condensing)					
Storage Temperature	-20 to +85°C					
Storage Humidity	85% RH(non-condensing)					
Withstanding Voltage	Primary-Secondary AC 1,500V for 1 minute Primary-Frame Ground AC 1,500V for 1 minute Secondary-Frame Ground AC 500V for 1 minute					
Isolation Resistance	Primary-Secondary-Frame Ground 50MΩ (minimum) by DC 500V insulation tester					
Vibration	5-10Hz:10mm double amplitude,10-55Hz:19.6m/s <sup>2</sup> ,20minutes' period for 60minutes each along X,Y,Z axes(non-operating)					
Shock	294m/s <sup>2</sup>					
Cooling	Convection					
? Leakage Current	1mA(maximum) at 25°C ,rated input/output and rated input frequency					
? Line Conducted Noise	Built to meet FCC Part15-B Class B					
? Safety						
? Weight (typical)	400g/enclosed type:490g					
? MTBF [H]	670,000					
? Switching Frequency[kHz](typical) *7	35					

Conditions:

\*1 at cold start

\*2 at DC 130V input and rated output

\*3 measured by a bayonet probe at output connector at 0 to 100MHz bandwidth

\*4 at -5 to +50°C /enclosed type: at -5 to +40°C

\*5 for 7hour period after 1hour warm-up at 25°C and rated input/output

\*6 when output current changed from 25% to 75% of rated output current rapidly at AC 100V input

\*7 variable on input voltage and load conditions

