

NAR-2200

1U server with PCI-Express Gigabit Ethernet, Gen.-2 Bypass and dual channel DDR2 Memory



FEATURE

- Up to Six GbE, 4x PCI-Express x1 with 2x 82541PI(GbE)
- Cost effective system with 2.5/3.5" HDD and Fan-less solution
- High computing performance with low power consumption
- Fulfill most Entry level Rack-mount platform requirement
- Supports Compact Flash and Disk on Module (DOM)
- Generation-2 Bypass function supported (Software control)
- Supports dual channel DDR2 533 up to 2GB

SPECIFICATION

CPU Board	- Support Intel® Celeron® M/Pentium M processors up to 2GHz - Intel® 915GME/910GML chipset with 533/400MHz FSB
System Memory	Dual channel 200-pin SODIMM sockets support DDR400/533MHz up to 2GB
Ethernet Port	- 4 PCI-E x1 GbE ports - 2 PCI FE or GbE ports
PCI Expansion	Optional
Storage Device	- CompactFlash - Disk on Module (DOM) - One SATA/IDE 2.5/3.5" HDD
Serial Port	- One RJ45 for system console - One 2x5 pin-connector
LCD Panel	Optional
LEDs	Power status, data access, Ethernet status (LNK/ACT), Ethernet speed (10/100/1000) and bypass
IDE	- One 40-pin IDE connector - Two SATA connectors
USB	Two USB 2.0 ports, front accessible
VGA	Built-in on-board 2x5 pin-header
Power	80W full-range AT
Dimension	428(W) x 255(D) x 44(H)mm 16.83"(W) x 10.04"(D) x 1.73"(H)
Packing Dimension	22.4"(W) x 24.4"(D) x 8.7"(H)
Operating Environment	- Temperature: 5 to 40°C (41 to 104°F) - Humidity 20% to 90%RH
Storage Environment	- Temperature: 0 to 70°C (32 to 158°F) - Humidity 5% to 95%RH
Certification	CE/FCC/UL



ORDERING GUIDE

Part No.	CPU	Chipset	Ethernet	Bypass	EZIO	PCI Exp.
NAR-2200-621	Intel® ULV Celeron® M 600MHz	910GML	4 GbE+2 FE	One bypass seg.	N/A	N/A
NAR-2200-601	Intel® Celeron® M / Pentium® M	915GME	6 GbE	One bypass seg.	N/A	N/A