

WIRING SCHEMATIC				WIRING SCHEMATIC			
P1 DB25F		P2 DB25F		P1 DB25F		P2 DB25F	
1		1	ſ	16		16	
2		2	ſ	17		17	
3		3		18		18	
4		4		19		19	
5		5		20		20	
6		6		21		21	
7		7		22		22	
8		8		23		23	
9		9		24		24	
10		10		25		25	
11		11		SHELL		SHELL	
12		12					
13		13					

14

15

14

15

		PARTS LIST	
ITEM NO.	QTY. REQ.	DESCRIPTION	
1	2	DB-25 FEMALE CONNECTOR	\triangle
2	2	SLOTTED JACK SCREW 5/16	
3	2	#4-40 HEXNUTS	

 \triangle

MATERIAL:

-DB25 FEMALE TO FEMALE:

CONNECTORS:

CONTACTS: GOLD PLATE OVER NICKEL SHELL: STEEL TIN PLATED

2. ALL DIMENSIONS ARE MAXIMUM AND SHOULD BE USED FOR REFERENCE ONLY.

SHAXON INDUSTRIES
4950 EAST HUNTER AVE.
ANAHEIM, CA. 92807

DESCRIPTION: GENDER CHANGER, LOW PROFILE, DB25	F-DB25F	CHK:	APRVD:	REV.:	DWG BY:	Q. NGUYEN
AGR	THIS DRAWING IS THE EXCLUSIVE PROPERTY OF SHAXON INDUSTRIES, INC. ITS ACCEPTANCE CONSTITUTES AN AGREEMENT THAT SHOULD BE TREATED AS A STRICTLY CONFIDENTIAL DOCUMENT TO BE USED FOR NO OTHER					09-29-98 OT SCALE
MATERIAL: OR UPO	POSE THAN TO AID IN THE ASSEMBLY OR OPERATION O DTHERWISE AS EXPRESSLY AUTHORIZED IN WRITING BY S N REQUEST AND IS NOT TO BE COMMUNICATED, DISCLO RITING BY SHAXON INDUSTRIES INC. AutoCAD Release I	SHAXON IND. INC SED OR COPIED	. THAT IT IS RETURNEI EXCEPT AS EXPRESSL'	D	PART NO.:	N25FF