

# AIIS-1240

PoE Compact System, Supports Intel® Core™ i7/i5/i3 CPU, 4-CH GbE PoE



## Features

- Intel® 3rd Core™ i7/i5/i3 CPU (LGA1155)
  - Powered device auto detection and classification
  - Supports IEEE 1588 & GigE Vision device
- 4-CH GbE PoE (Power over Ethernet), IEEE 802.3af compliant
  - Volume less than 3 Liter
  - Easier fan filter maintenance
  - Internal USB Type-A with lock design (Max. 49mm length)
  - Wall or DIN rail mounting kit (optional)
  - Build in G-sensor for vibration detection
- Compact & thoughtful design


## Specifications

Processor System	CPU	Core i7-3770	Core i5-3550S	Core i3-3220
	Core	4	4	2
	Base Frequency	3.4 GHz	3.0 GHz	3.3 GHz
	L3 Cache	8 MB	6 MB	3 MB
	Chipset	H61		
BIOS	AMI 64Mb SPI Flash			
Memory	Technology	Dual Channel DDR3 1066/1333 MHz (Non ECC)		
	Max. Capacity	16 GB (8 GB per DIMM)		
	Socket	204-pin SO-DIMM x 2		
Graphics	Chipset Integrated	Integrated Intel HD Graphics		
PoE	Controller	CH1 ~ CH4: Intel i210		
	Compliant	IEEE 802.3af		
	Power Output	15.4W per Channel		
Ethernet	Interface	10/100/1000 Mbps		
	Controller	LAN1: Intel 82579V, LAN2: Intel 82583V		
Storage	Internal 2.5" HDD Bay	1		
	CFast	1		
Front I/O	Display	VGA + DVI-D		
	USB	4 USB3.0		
	Serial	2 (RS-232, RS-422 or RS-485 via BIOS setting; RS-485 with auto-flow control)		
	DIO	8-CH (default), additional 32-CH (optional module AIIS-DIO32-00A1E)		
Rear I/O	USB	4 USB2.0		
	Serial	4 RS-232		
Watchdog Timer	Output	System reset		
	Interval	Programmable 1 ~ 255 sec/min		
Power Requirement	Power Type	ATX		
	Power Input Voltage	19 V <sub>DC</sub> ~ 24 V <sub>DC</sub>		
	Minimum Power Input	DC 19-24V @ 8-6.3A		
	Power Adapter	AC to DC, DC24V/9.16A, 220W (Optional)		
Cooling	System Fan	1 (6cm / 27.7 CFM)		
Miscellaneous	LED Indicators	Power, HDD, temperature		
	Control	Power on/off switch		
Environment	Operating Temperature	0 ~ 45° C (32 ~ 113° F)*	Non-operating -40 ~ 70° C (-40 ~ 158° F)	
	Humidity	10 ~ 95% @ 40° C, non-condensing	10 ~ 95% @ 60° C, non-condensing	
	Vibration	1Grms, random, 5-500Hz, 3 axes, 1 hr/axis	2G, sine wave, 5-500Hz, 3 axes, 1 hr/axis	
	Shock	10G, half sine wave, 11 ms duration		
	Physical Characteristics	Dimension (W x H x D)	232 x 70 x 175 mm (9.06" x 2.76" x 6.89")	
Weight		2.5 kg		


\* Depend on CPU

## Dimensions

Unit: mm [inch]




## Front View



## Internal View



## Rear View



## Ordering Information

Part Number	PoE Port	Display	USB 3.0/2.0	DIO	COM 232/422/485	COM 232
AIIS-1240-00A1E	4-CH	VGA+DVI-D	4 / 4	8-CH	2	4

## Optional Accessories

Part Number	Description
98R2124000E	DIN-Rail Bracket
1757004518-01	220Watt DC24 Adapter
AIIS-DIO32-00A1E	DIO module, 32-CH, 9-pin USB interface

Note: If there is no 19-24V<sub>DC</sub> source in your facility, this adapter is required to power on the system

## Packing List

Items	Part Number	Quantity
AIIS-1240 Bare System	AIIS-1240-00A1E	1
Startup Manual	2006S12400	1
Driver CD	206K124000	1
Wallmount Bracket	1960014487T004	2
Rubber Foot	1990012452S000	4
CPU Cooler	1960060620N001	1