

# HS-7260

Intel® Core™ 2 Duo/Celeron® M processor PCI-ISA Bus SBC w/CF, Mini PCIe, DVI-I/CRT/LVDS, Dual Gigabit Ethernet, Audio, 2 COM, 4 USB



## Features

- » Intel® Core™ 2 Duo/Celeron® M processor
- » 1 x SO-DIMM up to 2GB DDR2 SDRAM
- » Intel® 945GME/ICH7-M system chipset
- » 18-bit dual-channel LVDS
- » Dual Gigabit Ethernet
- » ALC202A Codec
- » Hardware Monitor function
- » Option for DVI-I display

## System

- CPU**  
Socket M for Intel® Core™ 2 Duo/Celeron® M processor
- Bus Interface**  
PCI-ISA Bus (no 3.3V output through Golden Finger)
- FSB**  
667/533MHz FSB
- BIOS**  
Award PnP Flash BIOS
- System Chipset**  
Intel® 945GME/ICH7-M
- I/O Chipset**  
Winbond W83627EHG
- System Memory**  
1 x 200-pin SO-DIMM, DDR2 667MHz, Max. 2GB
- Storage**  
1 x Type II CF socket
- Expansion Interface**  
1 x mini PCIe socket (option)
- GPIO**  
8-bit general purpose input/output port
- Watchdog Timer**  
Software programmable time-out intervals from 1~255 sec. or 1~255 min.
- H/W Status Monitor**  
Monitoring temperatures, voltages, and cooling fan status
- Power Function**  
AT/ATX power mode support
- Operating Temperature**  
0~60°C
- Operating Humidity**  
0~95%, non-condensing
- Board Size (LxW)**  
186 x 122 mm

## I/O Interface

- I/O Port**
  - 1 x RS-232
  - 1 x RS-232/422/485
  - 4 x USB2.0
  - 1 x IDE
  - 1 x FDD
  - 2 x SATA
  - 1 x Parallel
  - 1 x PS/2 for KB/MS
  - 1 x 6-pin connector for PS/2 KB/MS

## Display

- Chipset**  
Intel® 945GME integrated Intel® GMA950
- Display Memory**  
DVMT3.0 up to 224MB video memory
- LVDS**  
18-bit single/dual-channel
- DVI**  
Chrontel CH7307 (option)
- Resolution**  
VGA Mode: 2048 x 1536

## Audio

- Chipset**  
RealTek ALC202A
- Audio Interface**  
MIC In, Line Out

## Ethernet

- Chipset**  
Dual RealTek RTL8111C Gigabit Ethernet
- Ethernet Interface**  
2 x RJ-45

## Ordering Information

- HS-7260**  
PCI-ISA Bus SBC w/CF, CRT, Dual Gigabit Ethernet, Audio
- HS-7260/DVI-I**  
PCI-ISA Bus SBC w/CF, DVI-I, Dual Gigabit Ethernet, Audio
- Accessory Options**
  - IDE Cable, FDD Cable, SATA Cable, USB Cable, H=23mm Cooler