



Ampro XTX 830

Core™ Duo Computer-on-Module

Blazing Performance, Power Management



XTX 830

Choose Ampro XTX 830 for...

Modular, ultra high performance applications that require notebook-style power management.

Description

Ampro XTX 830 is a small, ultra high-performance, dual core processor module with advanced networking and high-performance graphics in a modular format that plugs into your existing ETX® baseboard with minimal design change.



- Up to 2GB DDR2 Memory
- PCI Express, SATA
- ACPI 2.0 with S3 support
- Latest chipset, without a complete baseboard re-design

For more information, pricing, and details on volume discounts, please call us at 1. 800. 966. 5200 or +1. 408. 360. 0200.

We'll immediately connect you to your local distributor.

Don't see the product you need?
Contact us at 1. 800. 966. 5200 or
+1. 408. 360. 0200 for information about
our semi-custom and custom solutions.

Ordering Information

MODEL	DESCRIPTION
XT4-830-R-22	1.86GHz Celeron™ M CPU, 1MB L2 Cache, PCI Express, PCI, ACPI
XT4-830-R-32	1.66GHz Core™ Duo CPU, 2MB L2 Cache, PCI Express, PCI, ACPI
XT4-830-L-22	1.86GHz QuickStart Kit (R-22 SBC, 1GB RAM, Software, Documentation, XTX Baseboard)
XT4-830-L-32	1.66GHz QuickStart Kit (R-32 SBC, 1GB RAM, Software, Documentation, XTX Baseboard)

Specifications

PROCESSORS

- Choice of
 - 1.66GHz Core™ Duo L2400
 - 1.86GHz Celeron™ M 440
- Cache – 2MB, 1MB Level 2
- Chipset – Intel 945GME/ICH7M
- FSB – 533MHz or 667MHz
- System Controllers – PC-compatible DMA and interrupt controllers and timers
- Watchdog Timer

MEMORY

- DRAM – Up to 2GB DDR2 667 SODIMM

BUS INTERFACE

- PCI Express 4 x1, PCI and LPC

I/O

- EIDE – Single PCI-bus Enhanced Ultra DMA 66/100 Synchronous IDE Interface supports up to two hard drives
- SATA – 2 ports
- Serial – 2 ports, TTL, transceivers on baseboard
- Parallel – EPP/ECP bidirectional port
- Floppy – Supports 1 or 2 drives, shared with parallel
- USB – 6 USB 2.0 ports
- Keyboard/Mouse – PS/2 interface
- Audio – AC97/HD speaker, mic, headphone

NETWORK INTERFACE

- Ethernet – Intel 82562 (10/100BaseT)

VIDEO INTERFACE

- Controller – Integrated Intel GMA 950
 - AGP 3D engine
 - Supports resolutions to 2048x1536
 - Up to 224MB DVMT Frame Buffer
- Multiple Display support
 - LVDS, TV-out, CRT

SOFTWARE & DEVELOPMENT TOOLS

- OS Support – Ampro Embedded Linux, Windows™ CE 6.0, 5.0, XP, XPe (See Web site for details)
- BIOS – AMI with ACPI 2.0 including S3

MECHANICAL

- Size – 95x114mm (3.7x4.5"); XTX form factor
- Power Requirements (with 512MB RAM, 100% Loaded)
 - 1.66GHz 3.5A @ 5V
 - 1.86GHz 5.1A @ 5V
- Environmental
 - Temperature (with adequate thermal solution and air flow)
 - Standard: 0° to +60°C
 - Storage: –20° to +75°C
- Board Thickness – .062" (1.6mm)



5215 Hellyer Ave., San Jose, CA 95138 Tel. 408.360.0200 Fax 408.360.0222 sales@ampro.com

NOTICE: The product specifications provided in this datasheet are subject to change without notice. Every effort has been made to ensure the accuracy of this document. Ampro Computers, Inc., makes no warranties, expressed or implied, regarding errors or admissions and assumes no legal liability or responsibility for loss or damage resulting from the use of this document's information. AMPRO is a registered trademark and CoreModule, LittleBoard, Little Board, MightyBoard, MightySystem, MiniModule, ReadyBoard, ReadyPanel and ReadySystem are trademarks of Ampro Computers, Inc. All other trademarks and registered trademarks are the property of their respective owners.

APR.08

www.ampro.com