



* The heat sink has been removed for photo purpose.

Features

- Supports VIA C3™ Processor up to 733MHz
- Integrated AGP 4X 2D/3D graphic accelerator
- Dual Channel TTL/LVDS TFT LCD
- 10/100Mbps Fast Ethernet
- Supports Type II CompactFlash™ Memory
- PC/104 expansion interface
- ISA interface



Specifications

System

■ CPU	VIA Eden Processor 300/733MHz
■ System Memory	144 pin SDRAM SODIMM x 1, Max. 512MB
■ Chipset	VIA VT8606 + VT82C686B
■ I/O Chipset	VT82C686B
■ BIOS	Award 256KB FLASH ROM
■ Ethernet	RTL8139D, 10/100Base-Tx RJ-45 connector x 1
■ SSD	Type II CompactFlash slot
■ Watchdog Timer	Generate a system reset
■ Expansion Interface	ISA Interface, PC/104 socket x 1
■ Battery	Lithium battery
■ H/W Status Monitoring	Supports power supply voltages, fan speed and temperature monitoring
■ Power Supply Voltage	+5V, +12V. AT / ATX
■ Board Size	7.3" (L) x 4.8" (W) (185 mm x 122 mm)
■ Gross Weight	0.66 lb. (0.3 kg)
■ Operating Temperature	32°F to 140°F (0°C to 60°C)

I/O

■ MIO	EIDE (UDMA100) x 1, FDD x 1, KB+Mouse x 1, RS-232 x 3, RS-232/422/485 x 1, Parallel x 1
■ IrDA	One IrDA Tx/Rx header
■ USB	Two 5x2 pin headers support 4 USB 1.1 ports

Display

■ Chip	VIA VT8606
■ Memory Size	Shared memory up to 32 MB
■ Resolution	up to 1600 x 1200 @ 16bpp colors for CRT
■ LCD Interface	36-bit TTL/LVDS TFT/DSTN LCD
■ Supports CRT and LCD Simultaneous Display	

Packing List

■ Short copper and support	9657666600
■ Jumper Cap	9657657000
■ Cable Accessory	9657657100
■ Quick Installation Guide	
■ Utility CD	