

Table 18.1: 3- or 4-Pole Screw Terminal Connections

Maximum Horsepower Ratings						Maximum Current Utilization Categories		No of Poles		Instantaneous Auxiliary Contacts		Catalog Number ▲	\$ Price	
Single Phase		Three Phase				Inductive AC3 Amperes	Resistive AC1 Amperes	N.O.	N.C.	N.O.	N.C.		AC Coils	DC Coils
115 V hp	230 V hp	200 V hp	230 V hp	460 V hp	575 V hp									
0.5	1	2	2	5	7.5	9	3	0	1	1	LC1D09 ◆◆◆	94.00	119.00	
—	—	—	—	—	—	—	4	0	—	—	LC1DT20 ◆	94.00	119.00	
—	—	—	—	—	—	—	2	2	—	—	LC1D098 ◆	94.00	119.00	
1	2	3	3	7.5	10	12	3	0	1	1	LC1D12 ◆◆◆	119.00	149.00	
—	—	—	—	—	—	—	4	0	—	—	LC1DT25 ◆	119.00	149.00	
—	—	—	—	—	—	—	2	2	—	—	LC1D128 ◆	119.00	149.00	
1	3	5	5	10	15	18	3	0	1	1	LC1D18 ◆★	136.00	160.00	
—	—	—	—	—	—	—	4	0	—	—	LC1DT32 ◆	149.00	183.00	
—	—	—	—	—	—	—	2	2	—	—	LC1D188 ◆	149.00	183.00	
2	3	7.5	7.5	15	20	25	3	0	1	1	LC1D25 ◆★	151.00	181.00	
—	—	—	—	—	—	—	4	0	—	—	LC1DT40 ◆	193.00	240.00	
—	—	—	—	—	—	—	2	2	—	—	LC1D258 ◆	193.00	240.00	
2	5	10	10	20	30	32	3	0	1	1	LC1D32 ◆★	172.00	213.00	
3	5	10	10	30	30	40	3	0	1	1	LC1D40A	218.00	275.00	
—	—	—	—	—	—	—	4	0	0	0	LC1DT60A	296.00	353.00	
3	7.5	15	15	40	40	50	3	0	1	1	LC1D50A	234.00	291.00	
5	10	20	20	40	50	65	3	0	1	1	LC1D65A	322.00	379.00	
—	—	—	—	—	—	—	4	0	0	0	LC1DT80A	446.00	503.00	
7.5	15	25	30	60	60	80	3	0	1	1	LC1D80	363.00	420.00	
—	—	—	—	—	—	—	4	0	—	—	LC1D80004 ■	489.00	524.00	
—	—	—	—	—	—	—	2	2	0	0	LC1D80008 ■	489.00	524.00	
—	—	30	40	75	100	115	3	0	1	1	LC1D115	479.00	479.00	
—	—	40	50	100	125	150	3	0	—	—	LC1D150	696.00	696.00	
—	—	—	—	—	—	—	4	0	0	0	LC1D115004	630.00	630.00	

- ▲ Complete catalog number with coil voltage code from table on page 18-6; example, LC1D09G7.
- For DC version of these devices replace the 'C' with 'P' (ex. LC1D80004** becomes LP1D80004**). This applies only to 80A 4 pole devices.
- ◆ On LC1D09 - LC1D65A and LC1DT20 through LC1DT80A, for ring tongue versions add '6' to the catalog number prior to adding the voltage code (ex. LC1D09G7 becomes LC1D096G7 and LC1D50AG7 becomes LC1D50A6G7). No price adder for this modification.
- ★ On LC1D09 - LC1D65A, for spring terminals versions add '3' to the catalog number prior to adding the voltage code (ex. LC1D12G7 becomes LC1D123G7 and LC1D40AG7 becomes LC1D40A3G7 - Note that 40A to 65A spring terminals are only on the control terminations and not on power terminations). No price adder for this modification.
- ▼ On LC1D09 and LC1D12 only, for slip-on connector versions add '9' to the catalog number prior to adding the voltage code (ex. LC1D09G7 becomes LC1D099G7). No price adder for this modification.

Table 18.2: TeSys D Overload Relays — Ambient Compensated, Bi-Metallic Direct Mount

Current Setting Range Amperes	For Direct Mounting to LC1...	Class 10 with Single Phase Sensitivity	Class 10 without Single Phase Sensitivity	Class 20 with Single Phase Sensitivity	Class 20 without Single Phase Sensitivity	\$ Price
0.10-0.16	D09-D32	LRD01	LR3D01	—	—	60.00
0.16-0.25		LRD02	LR3D02	—	—	
0.25-0.40		LRD03	LR3D03	—	—	
0.40-0.63		LRD04	LR3D04	—	—	
0.63-1		LRD05	LR3D05	—	—	
1-1.6		LRD06	LR3D06	—	—	
1.6-2.5		LRD07	LR3D07	—	—	
2.5-4		LRD08	LR3D08	LRD1508	LR3D1508A1	
4-6		LRD10	LR3D10	LRD1510	LR3D1510A1	
5.5-8		D09-D32	LRD12	LR3D12	LRD1512	
7-10	D09-D32	LRD14	LR3D14	LRD1514	LR3D1514A1	
9-13	D12-D32	LRD16	LR3D16	LRD1516	LR3D1516A1	
12-18	D18-D32	LRD21	LR3D21	LRD1521	LR3D1521A1	
16-24	D25-D32	LRD22	LR3D22	—	—	
17-25	D25-D32	—	—	LRD1522	LR3D1522A1	
23-32	D25-D32	LRD32	LR3D32	—	—	73.00
23-28	D25-D32	—	—	LRD1530	LR3D1530A1	
25-32	D25-D32	—	—	LRD1532	LR3D1532A1	
30-38	D32	LRD35	LR3D35	—	—	
9-13	D40A-D65A △	LRD313	LR3D313	LRD313L	—	107.00
12-18	D40A-D65A △	LRD318	LR3D318	LRD318L	—	
16-25	D40A-D65A △	LRD325	LR3D325	LRD325L	—	
23-32	D40A-D65A △	LRD332	LR3D332	LRD332L	—	
30-40	D40A-D65A △	LRD340	LR3D340	LRD340L	—	
37-50	D40A-D65A △	LRD350	LR3D350	LRD350L	—	
48-65	D40A-D65A △	LRD365	LR3D365	LRD365L	—	
17-25	D40-D80 □	LRD3322	LR3D3322	LR2D3522	LR3D3522	107.00
23-32	D40-D80 □	LRD3353	LR3D3353	LR2D3553	LR3D3553	
30-40	D40-D80 □	LRD3355	LR3D3355	LR2D3555	LR3D3555	
37-50	D50-D80 □	LRD3357	LR3D3357	LR2D3557	LR3D3557	
48-65	D50-D80 □	LRD3359	LR3D3359	LR2D3559	LR3D3559	
55-70	D65-D80	LRD3361	LR3D3361	LR2D3561	LR3D3561	
63-80	D65-D80	LRD3363	LR3D3363	LR2D3563	LR3D3563	127.00
80-104	D80	LRD3365	—	—	—	
80-104	D115-D150	LRD4365	—	—	—	
95-120	D115-D150	LRD4367	—	—	—	362.00
110-140	D150	LRD4369	—	—	—	

- △ Overload relays with Everlink termination - direct mount to D40A to D65A only.
- Direct mount to old D2 style D40 to D65 (no Everlink terminations) and to D80 only.

TeSys D contactor accessories pages 18-8 to 18-11
 TeSys D overload relay accessories page 18-16
 TeSys D replacement coils pages 18-17 to 18-19
 Dimensions pages 18-40 to 18-46
 TeSys T pages 16-91

18 IEC CONTACTORS AND STARTERS



LC1D09



LC1D093



LC1D40A



LC1D115



LRD22



LRD3



E164862
CCN NLDX



LR43364
Class 3211 04



	LC	D				
Full Voltage, Non-Reversing	1					
Full Voltage, Reversing	2					
TeSys D 3 Pole Contactors 9A to 150A						
Contactor AC-3 Full Load Amps (FLA)						
9A FLA		09				
12A FLA		12				
18A FLA		18				
25A FLA		25				
32A FLA		32				
38A FLA (not marketed in US)		38				
40A FLA		40				
50A FLA		50				
65A FLA		65				
80A FLA		80				
95A FLA (not marketed in US)		95				
115A FLA		115				
150A FLA		150				
Everlink Power Connection (40A to 65A only)			A			
No Everlink Power Connection (9A to 32A, 80A to 150A)			Blank			
Termination Options (choose one)						
Screw Termination				Blank		
Spring Terminations †				3		
Ring Tongue Terminations ●				6		
Slip-on Terminations (9A to 12A only)				9		
Coil Voltage (choose one)						
	AC Coils (50/60 Hz)		DC Coils (standard)		DC Coils low consumption available for 9 to 38 amp only	
	12V	J7	12V	JD	5V	AL
	21V	Z7	21V	ZD	12V	JL
	24V	B7	24V	BD	21V	ZL
	36V	C7	36V	CD	24V	BL
	42V	D7	48V	ED	48V	EL
	48V	E7	60V	ND	72V	SL
	60V	EE7	72V	SD	96V	DL
	100V	K7	110V	FD	110V	FL
	110V	F7	125V	GD	220V	ML
	115V	FE7	220V	MD	250V	UL
	120V	G7	250V	UD		
	127V	FC7	440V	RD		
	200V	L7				
	208V	LE7				
	220V	M7				
	230V	P7				
	240V	U7				
	277V	W7				
	380V	Q7				
	400V	V7				
	415V	N7				
	440V	R7				
	480V	T7				
	500V	S7				
	575V	SC7				
	600V	X7				
	660V	Y5				
		(50 Hz only)				

† On LC1D09 - LC1D65A, for spring terminals versions add '3' to the catalog number prior to adding the voltage code (ex. LC1D12G7 becomes LC1D123G7 and LC1D40AG7 becomes LC1D40A3G7 - Note that 40A to 65A spring terminals are only on the control terminations and not on power terminations). No price adder for this modification.

● On LC1D09 - LC1D65A and LC1DT20 through LC1DT80A, for ring tongue versions add '6' to the catalog number prior to adding the voltage code (ex. LC1D09G7 becomes LC1D096G7 and LC1D50AG7 becomes LC1D50A6G7). No price adder for this modification.

Note: To be used for interpretation of current catalog numbers only.