

F-Frame

F-Frame



Typical F-Frame Breaker



F-Frame Breaker with Electronic Trip Unit

45

Product Description

- All Eaton's Cutler-Hammer F-Frame Circuit Breakers by are HACR rated.
- All circuit breakers 10 through 30 amperes are suitable for HID (high intensity discharge) use.
- All F-Frame circuit breakers are suitable for reverse feed use

Technical Data and Specifications

Table 45-92. UL 489 Interrupting Capacity Ratings

Circuit Breaker Type	Number of Poles	Interrupting Capacity (kA Symmetrical Amperes)					
		Volts ac (50/60 Hz)				Volts dc ^①	
		240	277	480	600	125	250 ^{②③}
EDB	2, 3	22	—	—	—	10	—
EDS	2, 3	42	—	—	—	10	—
ED	2, 3	65	—	—	—	10	—
EDH	2, 3	100	—	—	—	10	—
EDC	2, 3	200	—	—	—	10	—
EHD	1	—	14	—	—	10	—
	2, 3	18	—	14	—	—	10
FDB	2, 3, 4	18	—	14	14	—	10
FD,	1	—	35	—	—	10	—
FDE ^④	2, 3, 4	65	—	35	18	—	10
HFD,	1	—	65	—	—	10	—
HFDE ^④	2, 3, 4	100	—	65	25	—	22
FDC ^⑤ ,	2, 3, 4	200	—	100	35	—	22
FDCE ^{④⑤}							

① dc ratings apply to substantially non-inductive circuits.

② 2-pole circuit breaker, or two poles of 3-pole circuit breaker.

③ Time constant is 3 milliseconds minimum at 10 kA and 8 milliseconds minimum at 22 kA.

④ Electronics available on 3-pole only.

⑤ Current limiting.

Table 45-93. IEC 157-1 (P1) Interrupting Capacity Ratings (P1)

Circuit Breaker Type	Number of Poles	Interrupting Capacity (kA Symmetrical Amperes)					
		Volts ac (50/60 Hz)				Volts dc ^⑥	
		220, 240	380, 415	440	500	125	250 ^{⑦⑧}
EDB	2, 3	22	—	—	—	10	—
EDS	2, 3	42	—	—	—	10	—
ED	2, 3	65	—	—	—	10	—
EDH	2, 3	100	—	—	—	10	—
EDC	2, 3	200	—	—	—	10	—
FDB	2, 3, 4	18	14	14	14	—	10
FD	1	35	—	—	—	10	—
	2, 3, 4	65	35	35	18	—	10
HFD	1	65	—	—	—	10	—
	2, 3, 4	100	65	65	25	—	22
FDC	2, 3, 4	200	100	100	35	—	22

⑥ dc ratings apply to substantially non-inductive circuits.

⑦ 2-pole circuit breaker, or two poles of 3-pole circuit breaker.

⑧ Time constant is 3 milliseconds minimum at 10 kA and 8 milliseconds minimum at 22 kA.

Table 45-94. Digitrip Electronic Trip Units

Circuit Breaker Type	Frame	Ratings
FDE, HFDE, FDCE	225	100, 110, 125, 150, 160, 175, 200, 225
FDE, HFDE, FDCE	160	60, 70, 80, 90, 100, 125, 150, 160
FDE, HFDE, FDCE	80	15, 20, 30, 40, 50, 60, 70, 80

F-Frame
Table 45-95. F-Frame Digitrip Specifications

Trip Unit Type	Digitrip RMS 310+	
rms Sensing	Yes	
Breaker Type		
Frame Ampere Range Interrupting Rating at 480 V	FDE 15 – 225 A 35, 65, 100 (kA)	
Protection		
Ordering Options	LS LSG	LSI LSIG
Fixed Rated Plug (I_n) Overtemperature Trip	No Yes	
Long Delay Protection (L)		
Adjustable Rating Plug (I_n) Long Delay Pickup Long Delay Time I^2t	No 40 – 100% Frame 2 – 24 Seconds	
Long Delay Time I^4t Long Delay Thermal Memory High Load Alarm	No Yes Yes	
Short Delay Protection (S)		
Short Delay Pickup	200 – 1000% x (I_r)	
Short Delay Time I^2t Short Delay Time Flat	Yes No	No Inst – 300 ms
Short Delay Time Z.S.I.	No	
Instantaneous Protection (I)		
Instantaneous Pickup Discriminator Instantaneous Override	No No Yes	
Ground Fault Protection (G)		
Ground Fault Alarm Ground Fault Pickup Ground Fault Delay I^2t	No 20 – 100% Frame No	
Ground Fault Delay Flat Ground Fault Z.S.I. Ground Fault Thermal Memory	Inst – 300 ms No Yes	
System Diagnostics		
Cause of Trip LEDs Magnitude of Trip Information Remote Signal Contacts	No No No	
System Monitoring		
Digital Display Current Voltage	No No No	
Power and Energy Power Quality Harmonics Power Factor	No No No	
Communications		
PowerNet	No	
Testing		
Testing Method	Test Kit	

 I_n = Rating Plug
 I_r = LDPU Setting x I_n

F-Frame

Dimensions/Weights

Table 45-96. Dimensions in Inches (mm)

Number of Poles	Width	Height	Depth
1	1.38 (35.1)	6.00 (152.4)	3.38 (86.0)
2	2.75 (70.0)	6.00 (152.4)	3.38 (86.0)
3	4.13 (105.0)	6.00 (152.4)	3.38 (86.0)
4	5.50 (139.7)	6.00 (152.4)	3.38 (86.0)

Table 45-97. Approximate Shipping Weight, Lbs. (kg)

Breaker Type	Number of Poles			
	1	2	3	4
ED, EDB, EDS, EDH, EDC	—	3 (1.4)	4.5 (2.0)	—
EHD, FDB, FD, HFD, FDC	2 (.9)	3 (1.4)	4.5 (2.0)	6 (2.7)
FDE, HFDE, FDCE	—	—	4.5 (2.0)	—

Product Selection

This information is presented only as an aid to understanding Catalog Numbers. It is not to be used to build Catalog Numbers for circuit breakers or trip units.

Table 45-98. Circuit Breaker Catalog Numbering System

