


# EmCORE-i315

Embedded 386SX Tiny Board with 2S/DOC/4MB DRAM /Digital IO



## Features

- ALi M6117C System On Chip, compatible with 386SX-40 core
- 4 MB EDO Memory soldered on board
- LAN 10 Mbps, Realtek 8019AS 16-bit Digital I/O
- DiskOnChip Socket Tiny board of New High Integration 386 system



## System

<b>CPU</b>	386SX onboard 40MHz CPU
<b>Chipset</b>	ALi M6117C (Embedded CPU, 386SX-40 Compatible)
<b>Memory</b>	4MB of EDO RAM Standard onboard
<b>BIOS</b>	AMI BIOS
<b>Watchdog Timer</b>	From 30.5us to 512 seconds
<b>Other</b>	Real Time Clock with Lithium Battery Backup

## I/O

<b>Serial port</b>	1 x RS-232 port (COM1) 1 x RS-232/485 port (COM2)
<b>Parallel port</b>	SPP/EPP/ECP mode
<b>Keyboard</b>	1 x Keyboard port
<b>Digital I/O</b>	16bit Digital Input/Output
<b>Other</b>	Power LED Active LED Buzzer

## Ethernet


<b>Chipset</b>	Realtek 8019AS Single chip, 10Mbps, NE2000 compatible
----------------	---

## Flash Disk

<b>Flash Disk</b>	One Socket for Flash ROM or Disk On Chip
-------------------	--

## Mechanical & Environmental

<b>Power Consumption</b>	5V/400mA (Max.)
<b>Operating Temp.</b>	-20 ~ 70°C (-4 ~ 158°F)
<b>Dimension (L x W)</b>	100 x 71.6 mm (3.94" x 2.82")



Component Side

## Ordering Information

<b>EmCORE-i315DL</b>	386SX onboard 40MHz CPU with 4 MB EDO, Ethernet 2 serial ports and Disk on Chip Socket
----------------------	---