



## PICMG® 2.16 PSB System Processor Blade

### CompactPCI



Diversified Technology's CPB4612 PICMG 2.16-compliant packet switched backplane (PSB) processor blade combines high performance with low power for telecom and Internet IP-based applications.

The CPB4612 features the low power, high performance Intel® Pentium® M processor with speeds ranging up to 1.8GHz and 2MB L2 cache. The CPB4612 is based on the Intel® 855GME chipset with 400MHz front side bus. System memory of up to 2GB is supported via two PC-2700 SO-DIMMs. Onboard are dual 100/1000Mbps Ethernet ports routed according to PICMG 2.16, one 10/100Mbps Ethernet port available at the front panel, an Ultra-ATA IDE interface, Serial ATA, two PMC sites (one 64-bit/66MHz and one 32-bit/33MHz), High Speed USB, and serial ports. The CPB4612 also includes a two-stage watchdog timer for enhanced system reliability.

The CPB4612 has a universal PCI bridge to the backplane and can therefore operate in any slot of a PICMG® 2.16-compliant Packet Switched Backplane (PSB). PICMG® 2.9 system management is also supported via a satellite management controller.

Part of DTI's PlexSys family of PSB products, the CPB4612 was validated in DTI's PlexSys-4, 4U general purpose, carrier grade computing platform with CSB4240 Ethernet level 2/3 switch. The IPMI 1.5-compliant Baseboard Management Controller (BMC), when used with the CCM3402 chassis management module supports a comprehensive, protected lights-out management scheme.

The CPB4612 system/peripheral processor blade is a cost effective choice for application developers addressing high performance, converging Telecom and Internet IP-based markets such as VPN switches, media gateways, 2.5G/3G wireless, server clusters, IP DSLAM and voice/video/data servers.

### Product Features

#### Form Factor

CompactPCI CPU Blade based on the Intel® Pentium® M processor

#### CPU/Cache

Intel® Pentium® M processor with max speeds of 1.8GHz and up to 2MB L2 cache

#### Bus Interface

- Intel 855GME Chipset
- 400MHz Front Side Bus; 64-bit/66MHz CompactPCI Bus interface

#### Memory

- Two SO-DIMM sockets
- 128MB to 2GB of total memory

#### I/O

- Two 100/1000 Ethernet Interfaces on 2.16 Switched Fabric
- 10/100 Ethernet Interface
- Ultra-ATA IDE interface
- Serial ATA
- 2 PMC Sites
- High Speed USB
- Serial Ports

#### BIOS

AMI BIOS

#### Physical Dimensions:

9.2" x 6.3" x 0.8"

#### OS Support

Windows 2000, Windows NT, Windows XP, Red Hat Linux, Solaris, QNX

#### Warranty

Parts and labor covered for 2 years

**CPU / Cache**

- Intel® Pentium® M processor with max speeds of 1.8GHz and up to 2MB L2 cache
- 32KB internal L1 cache; 1 or 2MB 64-bit on-die L2 Cache

**Bus Interface**

- Intel® 855GME Chipset
- 400MHz Front Side Bus; 64-bit/66MHz CompactPCI Bus interface
- 5V/3V CompactPCI signaling as host
- Supports one onboard 64-bit/66MHz 3.3V PMC card
- Supports one onboard 32-bit/33MHz 3.3V/5V PMC card

**Memory**

- Two SO-DIMM sockets
- ECC support with x72 DIMMs
- 128MB to 2GB of total memory
- PC-1600, PC-2100, and PC-2700 memory speeds

**Data Path**

- 64-bit/400MHz on CPU and memory bus
- 64-bit/66MHz on off-board CompactPCI bus;
- 64-bit/66MHz on onboard PCI bus

**Flash Memory**

- 1MB Flash for BIOS

**Ethernet**

- Two 100/1000 Ethernet Interfaces on 2.16 Switched Fabric
- 10/100 Ethernet Interface

**Peripherals and I/O Interface**

- 2.5" IDE HDD drive mounted on board or 32-bit/33MHz IEEE P1386.1 PMC site
- 64-bit/66MHz PMC site

I/O Interface	Front Panel	Rear Panel
COM 1	DB9	N/A
COM 2	N/A	J5
USB 0	USB Conn	N/A
USB 1	N/A	J5
USB 2	N/A	J5
EIDE	N/A	J5
Gigabit Ethernet	N/A	J3
Gigabit Ethernet	N/A	J3
10/100 Ethernet	RJ-45	
S-ATA	N/A	J5
CRT	N/A	J5

**Clock / Calendar**

- Real-time clock with 256 byte battery backup CMOS RAM

**Supervisory**

- Two-stage programmable watchdog timer drives NMI or "INIT" on 1st stage, hardware reset on 2nd stage

**Interoperability**

- Validated to operate in a PICMG 2.16-compliant system platform such as DTI's cPS-4081
- DTI's cSB-4240 24-port level 2/3 Ethernet Switch Blade
- 3rd party PSB products

**OS Compatibility**

Windows 2000, Windows NT, Windows XP, Red Hat Linux, Solaris, QNX

**BIOS**

- AMI BIOS
- Console redirection (disabled by default - video to RTM)
- PCI 2.2
- ACPI 1.0b and 2.0
- SMBIOS 2.3.1
- PnP 1.0a

**BIOS (cont'd)**

- Multi-boot Support (Floppy, HD, CD, USB, Network)
- Legacy USB Support
- S.M.A.R.T. Support
- Pop-up Boot Menu
- PXE 2.1 Boot Rom

**Management**

- Integrated IPMI compliant satellite management controller
- Communicates with system management BMC or host processor
- Compliant with PICMG 2.9

**Mechanical**

- 9.2 in. x 6.3 in. 0.8 in. (233.35 mm x 160 mm x 20.32 mm)
- 6U x 4HP
- Conforms to PICMG 2.0 R3.0 (Core), 2.9 (Management) 2.12 (SW interoperability), 2.15 (PTMC) and 2.16 R1.0 (PSB) specifications

**Power Requirements**

Max Power Dissipation		48.2W
ICC typ.	+5V	6.89A
	+3.3V	2.39A

**Environmental****Operating (with HD)**

- Temperature: 0° to 50°C full speed up to 70°C with speed throttling
- Humidity (RNC): up to 98%
- Altitude: 8,000ft @ 70°C / 25,000ft @ 25°C
- Vibration: 5-100Hz @1g Random RTCA DO-160D, Zone 1, Category C 1.9gRMS
- Shock: 10g half-sine shock for 11ms, 3 in each direction 6g saw-tooth for 6 and 11 ms, 3 in each direction

**Storage and Transit (in approved packaging)**

- Temperature: -55°C to 85°C
- Altitude: 15240m / 50,000ft
- Shock: 24" free fall, 40g half-sine shock for 6ms, 500 in each direction
- Vibration: 0.5g 5-50Hz, 3g 50-500Hz Random mode 5-20Hz @ .01g2/Hz ; 20-500 with -3dB slope

**Reliability and Serviceability**

- MTBF: 237,399 hours @ 25°C (performed to Issue 6, Method I, Case 3 of the Bellcore IR Program)
- 2 year limited warranty

**Regulatory Compliance**

- Designed for NEBS/ETSI Compliance
- CE Certificate of Incorporation
- Safety: cUL-US 60950-1; EN/IEC 60950-1
- EMI/EMC: FCC 47 CFR Part 15 Class A; EN 55024:1998, EN 61000-3-2, EN 61000-3-3, EN 55022:1998, CISPR22:1997, AS/NZS3548:1995

**Ordering Information****CPB4612/1100 \***

SBC with 1.1GHz/400MHz Intel® Pentium® M processor and 1MB L2 cache

**CPB4612/1800 \***

SBC with 1.8GHz/400MHz Intel® Pentium® M processor 745 and 2MB L2 cache

\* long life-cycle support

**Options**

CRT4612, 6U x 4HP Rear I/O Transition Module

All products are shipped FOB factory (MS). Specifications subject to change without notice. Trademarks are the property of their respective owners. (C) Copyright 2007 by Diversified Technology, Inc. All rights reserved.