



\* The above picture demonstrates HSB-660S.

### Features

- Supports Socket 370 based Intel® Pentium® III / Celeron® / VIA C3™ Processor
- Dual RJ-45 Ethernet connectors onboard, 10/100Mbps and Gigabit supported
- Supports Type II CompactFlash™ Memory
- PC/104 expansion interface
- 4 USB Ports
- PCISA (HSB-660S) or ISA (HSB-660I) interface



### Specifications

#### System

- **CPU** Socket 370 based Pentium III / Celeron (.13 μ / .18μ) Processor up to 1.4GHz and VIA C3 Processor up to 1.1GHz with FSB 66/100/133MHz
- **System Memory** 168 pin SDRAM DIMM x 1, Max. 512MB (PC-133)
- **Chipset** VIA VT8606 + VT82C686B
- **I/O Chipset** VIA VT82C686B
- **BIOS** Award 512KB FLASH ROM
- **Ethernet**
  - Choice 1:** RTL8139DL + RTL8100C, 10/100Base-Tx RJ-45 connector x 2
  - Choice 2:** Intel 82551ER + RTL8110S, 10/100Base-Tx RJ-45 connector x 1 and 10/100/1000Base-Tx RJ-45 connector x 1
- **SSD** Type II CompactFlash slot
- **Expansion Interface** PCISA (HSB-660S) interface, ISA (HSB-660I) interface, PC/104 socket x 1
- **Battery** Lithium battery
- **H/W Status Monitoring** Supports power supply voltages, fan speed and temperature monitoring
- **Power Supply Voltage** +5V, +12V, -5V, -12V. AT / ATX
- **Board Size** 7.3" (L) X 4.8" (W) (185 mm X 122 mm)
- **Gross Weight** 0.66 lb. (0.3 Kg)
- **Operating Temperature** 32°F to 140°F (0°C to 60°C)

#### I/O

- **MIO** EIDE(UDMA100 ) x 1, FDD x 1, KB+Mouse x 1, RS-232 x 1, RS-232/422/485 x 1, Parallel x 1
- **IrDA** One IrDA Tx/Rx header
- **Audio** Realtek ALC201 AC-97 multi-channel CODEC
- **USB** Two 5x2 pin headers support 4 USB 1.1 ports

#### Display

- **Chip** VIA VT8606
- **Memory Size** Shared memory up to 32MB
- **Resolution** up to 1600 x 1200@ 16bpp colors for CRT up to 1024 x 768@ 18bpp colors for LCD
- **LCD Interface** 36-bit TTL TFT LCD
- **Supports CRT and LCD simultaneous display**
- **Supports CRT and LCD dual view**

### Packing List

- Short-copper and support 9657000300
- Jumper Cap 9657666600
- HDD Cable 1701400453
- FDD Cable 1701340702
- Y-Cable (Keyboard and Mouse) 1700060192
- USB Cable 1709100201
- LPT Cable 1701010302
- Audio Cable 1709140300
- Quick Installation Guide
- Utility CD