

IAC-F850

Full-Size PICMG 1.0 SBC, Intel Core 2 Duo, Dual Core Pentium 4 LGA775 with VGA/ SATA/ LAN/ USB/ CF/ COM/ Mini-PCI and optional Audio/ DVI/ TV-Out/ S-Video and LVDS

VGA

SATA

Gb LAN

USB

CF

COM


Audio

SDVO

DVI


TV-Out

S-Video



FEATURES

- Support Intel Core 2 Duo, Dual Core Pentium 4/D
- Intel 82945G chipset with FSB 533/800/1066MHz supports Hyper-Threading Technology
- Two DIMM up to 2GB DDR2 400/533/667 Non-ECC SDRAM
- SDVO supports optional DVI or LVDS / TV-out
- Dual Intel 82573L 10/100/1000Mbps LAN
- Type I/II CF, Mini-PCI socket
- PICMG 1.0 Compliant



FEATURE DESCRIPTION

Platform	Form Factor	Full-size, PICMG 1.0
	Processor	Supports LGA775 Intel Core 2 Duo, Dual Core Pentium 4/D with 533/800/1066MHz FSB
	Chipset	Intel® 82945G / 82801GB ICH7R
	BIOS	Award Flash BIOS
	Cache Memory	Processor Built-in
System Memory	Technology	DDR2 400/533/667 SDRAM, Dual-Channel
	Max Capacity	2GB
	Socket	240-pin DIMM x2
Storage Interface	Hard Drive Interface	IDE x1, Serial ATA II x4
	SSD (CF Socket)	CompactFlash III x1
Networking	Speed	10/100/1000 Mbps
	I/O	RJ45 x1 , Option RJ45 x1 on Bracket
	Controller	Intel 82573L
Display	Controller	Intel® 82945G GMCH integrated Graphic Media Accelerator 950 built-in high quality 2D/3D engine and High definition streams for MPEG playback
	Shared memory	DVMT(UMA)mode, 1MB/8MB of memory Pre-allocated
	Output	VGA, optional DVI or LVDS and TV-out
Audio	Codec	Realtek ALC203 AC97 audio codec
	I/O	Mic-in, Line-in, Speaker-out via add on bracket Module
I/O Interface	Floppy Drive Interface	FDD header 2.0mm x 1
	Serial Port	RS-232 x1, RS-232/422/485 x1
	Parallel Port	LPT Pin Header 2.54mm x 1
	Universal Serial Bus	6 (v 2.0) Pin headers, 2 ports
	Serial-ATA	4
	Digital I/O	4bit Digital I/O with pin-header (4 in/4 out)
	Bus interface	PCI /ISA
	IR Interface	115k bps, IrDA 1.0 compliant with pin-header connector
	Keyboard	Mini-DIN PS/2
	Mouse	Mini-DIN PS/2
	Hardware Monitoring	Controller
RTC		RTC with Li-Battery
Watchdog timer		256-level time-out intervals
Cooling	Heatsink & Fan	
Expansion	Mini-PCI x1	
Environmental Parameters	Temperature, ambient operating	0~60°C (32~140°F)
	Humidity (RH), ambient operating	5~95% relative humidity, non-condensing
	Storage Temperature	-20~70°C (-4~158°F)
Physical Dimensions	Dimensions	338x122mm (13.3" x 4.8")
	Input	+12V ,+5V,-12V power input
Power	Form Factor	ATX support
	Compliance	CE, RoHS

ORDERING INFORMATION

IAC-F850A	2 x Gb LAN + Audio module
IAC-F850B	1 x Gb LAN
IAC-SL01	Audio and Gb LAN module
IAC-LT01 (IAC-F850A Only)	LVDS / TV-Out / S-Video output module
IAC-DV01 (IAC-F850B Only)	DVI module (note can only select either IAC-DV01 or IAC-LT01)

About Lanner

Founded in 1986 and publicly listed (TAIEX 6245) since 2003, Lanner Electronics Inc. is an ISO 9001 certified designer and manufacturer of reliable, frontline security, storage and applied computing platforms and solutions. With headquarters in Taipei, Taiwan and branches in the U.S., India, and China, Lanner is uniquely positioned to deliver custom technical solutions with localized, value-added service.

Contact information

Lanner Electronics Inc
7F, 173, Section 2 Datong road
Sijhih City, Taipei County 221, Taiwan

T +886 2 86926060

F +886 2 86926101

E sales@lannerinc.com

W www.lannerinc.com