



















IP400

Flex ATX COM Express Baseboard

Features

- Winbond W83627EHG
- Watchdog timer, 4-in / 4-out digital I/O
- 1 x PCI-E 16, 1x PCI-E 1, 2x PCI (32-bit) slots
- Marvell 88E8053 PCI-E GbE for LAN2
- NS LM4940 2W stereo audio amplifier
- Edge connectors for VGA, COM1, dual USB, dual RJ45, PS/2, audio RCA, SPDIF, S-Video and TV out RCA
 Board connectors for IDE, 2x LVDS, 6x USB, FDD, LPT,
- Board connectors for IDE, 2x LVDS, 6x USB, FDD, LPT, IrDA and COM Express Type II connectors
- 190mm x 228mm

Ordering Information

IP400-R: Flex ATX COM Express Baseboard with Marvell 88E8053 PCI-E GbE

IP100P-R

5.25" Disk-Size ETX Baseboard

Features

- VGA CRT/LVDS connectors, 4x serial ports
- DiskOnChip[®], Digital I/O, IrDA
- 4x USB, PS/2 keyboard/mouse, PCI slot
- FDD/IDE/LPT, PC/104 interface
- 203mm x 146mm

Ordering Information

IP100P-R: 5.25" Disk-Size ETX Baseboard w/o LAN

IB10: Cable kit for IP100

IBD: RJ-45 cable w/ bracket

IBLD: Dual RJ-45 cable w/ bracket