


Ali M6117C



Features

- Onboard ALi M6117C, 386SX-40 Compatible
- 24-bit TTL TFT/DSTN/MONO LCD
- Supports DiskOnChip[®] Memory
- 2 COM Ports
- +5V Only Operation



Specifications

System	
Processor	Onboard ALi M6117C, 386SX-40 compatible
System Memory	Onboard 4MB/8MB EDO DRAM
Chipset	ALi M6117C
I/O Chipset	ITE 8661F
BIOS	AMI 128KB FLASH ROM
Watchdog Timer	Generates a time-out system reset, setting via software
SSD	DiskOnChip [®] up to 1GB
Expansion Interface	PC/104 socket x 1
Battery	Lithium battery
Power Requirement	+5V/AT
Board Size	3.55"(L) x 3.775"(W) (90mm x 96mm)
Gross Weight	0.6lb (0.25kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Display	
Chipset	C&T 65545
Memory	Built-in 512KB DRAM
Resolutions	up to 800 x 600@256 colors for CRT & LCD
LCD Interface	up to 24-bit TTL TFT/DSTN/MONO LCD
I/O	
MIO	IDE x 1, Floppy Disk Drive x 1, Keyboard+Mouse x 1, RS-232 x 1, RS-232/422/485 x 1, Parallel x 1

Packing List

- **9681333601**
Cable Kit (IDE Cable, Floppy Disk Drive Cable, Serial Port Cable x 2, Parallel Port Cable, Keyboard/Mouse Cable, VGA Cable)
- **Quick Installation Guide**
- **Utility CD**
- **PFM-336I**

Ordering Information

- **PCM-3336-A11**
PC/104 CPU Module, 386SX-40, Onboard 4MB DRAM, with DOC