
SBC81826

Socket 478 Intel® Pentium® 4/Celeron® with DDR/VGA/LAN



## **Specifications**

Processor/Cache	* Intel <sup>®</sup> Pentium <sup>®</sup> 4/ Celeron <sup>®</sup> processor at 400/533/800MHz FSE		
	* Supports Intel <sup>®</sup> Hyper-Threading technology		
Chipset	Intel <sup>®</sup> 865G and 82801EB ICH5		
System Memory	Two 184-pin DIMMS socket max. up to 2GB of DDR 266/333/400		
	SDRAM		
BIOS	Award 4M bit plug & play BIOS		
EIDE	Two ATA-100 channels		
Serial ATA	Two Serial ATA channels		
Super I/O	Controller : Winbond W83627HF		
	-1 x IrDA port -1 x floppy drive		
	-1 x SPP/EPP/ECP parallel port     -2 x RS-232 ports		
USB	Four USB ports (2.0)		
IrDA	One IrDA pin header for wireless communications		
VGA	Intel <sup>®</sup> 865G integrated graphic function		
LAN	Controller : Intel <sup>®</sup> 1 CH 5 with 82547GI PHY supports		
	10/100/1000 Base-T		
Connectors	* RJ-45 : 1port		
	* Serial ATA port : 2ports		
	* Mini DIN : 1 x PS/2 mouse and PS/2 keyboard		
	* Pin-header : 4 x USB (2 x 9-pin)		
	* Box-header : Serial port(2 x 10-pin), Parallel port(1 x 26-pin),		
	* FDD(1 x 34-pin), EIDE(2 X 40-pin), PS/2 keyboard(1 x 5-pin).		
	* Power connector : SB5V ATX power connector (1 x 4-pin)		
Hardware	Controller : Winbond W83627HF Monitoring for CPU and		
Monitoring	system temperature, voltages and fan speed		
Watchdog Timer	256 Levels watchdog Timer selectable with Reset/NMI		
Other Features	ITE 8888F PCI-ISA bridge for ISA expansion		
Mechanical	338 x 122mm(13.3" x 4.8"); Conforms to PCI Rev. 2.1 and		
	PICMG Rev. 2.0 standards		
Environmental	Operating temperature: 0°C to 60°C (32°F to 140°F);		
	Storage temperature: -20°C to 80°C (-68°F to 176°F)		
	Relative humidity: 10% to 90% (non-condensing)		

\*Note on the CPU Fan-Cooler: The position of retention module on SBC81826 is closer to the edge of PCB than usual, and Intel's standard CPU fan-cooler may have interference with slot on the backplane. Slim or short type of CPU fan-cooler with shorter clip is suggested.

#### **Features**

- Intel<sup>®</sup> 865G chipset supports FSB 400/533/800MHz
- Intel<sup>®</sup> Pentium<sup>®</sup> / Celeron<sup>®</sup> 4 processor supported
- Two-184pin DIMM sockets support up to 2GB
- Intel<sup>®</sup> 865G integrated video function
- Intel<sup>®</sup> 82547GI 10/100/1000 Base-Tx Ethernet control
- AC'97 audio codec
- Two serial ATA ports support data transfer rates up to 150MB/s

### **Ordering Information**

Model	VGA	LAN
SBC81826VG	V	1 x10/100/1000Mbps

# **Optional Accessories**

Audio card	
Audio cable	
P4 CPU fan-cooler with shorten clip	

## **Packing List**

FDD cable x 1		
Ultra ATA 66/100 HDD cable x 1		
Printer + COM cable x 1		
Y cable for PS/2 mouse & keyboard x 1		
Dual-USB port cable with bracket x 1		
ATX power control cable x 1(4pin to 6-pin)		
Serial ATA cable x 1		
Quick manual x 1		
Utility CD x 1		