



## Features

- ✓ Intel 915GME + ICH6M
- ✓ Support Pentium/Celeron M
- ✓ VGA/DVI/LVDS
- ✓ 2 x Giga LAN
- ✓ PCI-104 Interface
- ✓ Anti-Shock 2.5" HDD Mounting Kit
- ✓ COM, USB2.0, GPIO, SATA, IDE, CFII, Audio

## Specification

### System

<b>CPU</b>	Support Intel Pentium/Celeron M
<b>Chipset</b>	Intel 915GME + Intel ICH6M
<b>Front Side Bus</b>	400/533MHz
<b>Memory</b>	<ul style="list-style-type: none"> <li>• 1 x 200-pin SO-DIMM socket support 400/533MHz DDR2 SDRAM up to 1GB</li> <li>• 1GB pre-installed</li> </ul>

### Video

<b>Graphic Controller</b>	Intel 915GME integrated GMA 900 graphic controller
<b>Video Memory</b>	DVMT 3.0, Maximum 128MB shared.
<b>Video Interface</b>	<ul style="list-style-type: none"> <li>• 1 x VGA port (DB15)</li> <li>• 1 x DVI port</li> <li>• 1 x Dual Channel 18-bit LVDS port</li> </ul>

### Storage

<b>IDE</b>	1 x E-IDE (44-pin)
<b>SATA</b>	1 x SATA I port
<b>CF</b>	1 x External Compact Flash Type I/II slot
<b>Disk Bay</b>	1 x Anti-shock 2.5" HDD/SSD bracket

### Communication

<b>Ethernet</b>	2 x Gbps RJ45 with LED, Intel 82574L
<b>USB</b>	4 x USB2.0 (2 x external port, 2 x pin header)
<b>Serial Port</b>	<ul style="list-style-type: none"> <li>• 1 x RS-232/422/485 (DB9) (jumper-selectable)</li> <li>• 3 x RS-232 (DB9)</li> <li>• Automatic RS-485 data flow control</li> </ul>

### Expansion

<b>PCI Slot</b>	1 x PCI-104
<b>PCI Express Slot</b>	-
<b>miniPCIe</b>	-

### Other Feature

<b>PS/2</b>	1 x PS/2
<b>Audio</b>	Line -Out
<b>Hardware</b>	<ul style="list-style-type: none"> <li>• CPU voltage</li> </ul>
<b>Monitoring</b>	<ul style="list-style-type: none"> <li>• CPU and system temperature</li> </ul>
<b>WatchDog Timer</b>	Software programmable 1~255 sec.
<b>Indicator</b>	HDD and Power LED
<b>GPIO</b>	8-bit Digital I/O

### Power Requirement

<b>Power Input</b>	12 (+/-5%) VDC, Lockable DC jack
<b>Power Adaptor</b>	100~240VAC, 60W power adaptor
<b>Power Consumption</b>	47W without external devices

### Software

<b>OS Support</b>	Windows XP/XP Embedded/2000/CE, Linux
-------------------	---------------------------------------

### Mechanical & Environment

<b>Thermal Design</b>	Fanless
<b>Chassis Material</b>	Aluminum
<b>Dimension (W x D x H)</b>	251mm x 165mm x 67mm (9.89" x 6.50" x 2.64")
<b>Weight</b>	
<b>Operating Temp.</b>	Net: 2.0kg (4.5Lb)
<b>Storage Temp.</b>	0~50°C (32~122°F)
<b>Relative Humidity</b>	-20~70°C (-4~158°F)
<b>Safety</b>	0 to 90% @ 40°C, non-condensing CE, FCC class A

### Packing List

- 1 x AR-ES5230FL
- 1 x Quick user guide
- 1 x Utility CD
- 1GB memory pre-installed
- 1 x 2.5" anti-shock HDD mounting kit
- 1 x 2.5" HDD cable (44-pin)
- 1 x PS/2 keyboard and mouse cable
- 1 x Power adaptor
- 1 x AC power cord (Optional for USA/EU/UK type)
- 2 x Mounting bracket
- 2 x Screw pack

### Ordering Information

<b>AR-ES5230FLPM18</b>	AR-ES5230FL with Intel Pentium M 745 1.80GHz, 1GB DDR2 and 60W power adapter
<b>AR-ES5230FLPM18-W</b>	AR-ES5230FL with Intel Pentium M 745 1.80GHz, 1GB DDR2 and 9-32V DC power module
<b>AR-ES5230FLPM16</b>	AR-ES5230FL with Intel Pentium M 1.60GHz, 1GB DDR2 and 60W power adapter
<b>AR-ES5230FLPM16-W</b>	AR-ES5230FL with Intel Pentium M 1.60GHz, 1GB DDR2 and 9-32V DC power module
<b>AR-ES5230FLCM15</b>	AR-ES5230FL with Intel Celeron M 370 1.50GHz, 1GB DDR2 and 60W power adapter
<b>AR-ES5230FLCM15-W</b>	AR-ES5230FL with Intel Celeron M 370 1.50GHz, 1GB DDR2 and 9-32V DC power module