# > KT780/ATX

AMD Athlon™64 & AMD Phenom™ Single to Quad Core Basic ATX motherboard with 3 years longevity







- ➤ AMD Athlon™64 & AMD Phenom™ Single to Quad Core CPU
- > Up to 32GB of memory with ECC support for increased datasecurity
- > 3 years of availability
- ➤ AMD RS780 + SB700 Chipset with Hyperflash support for fast OS boot
- > ATI Radeon™ HD 3200 Graphics Core w. PCI-Express 16x 2.0 Support
- Optional HDMI interface
- ➤ Up to 2x 10/100/1000 Mbps Ethernet
- Trusted Platform Module (TPM) Onboard
- ➤ 12x USB2.0, 6x SATA, 4x PCI slot & 1x PCI Express x4



# HET799/ATMEDSCORED. Hat as for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is believed to be accurate, however, no responsibility is assumed for information purposes only and or product names are tandemarks or registered trademarks of their respective owners. DIMM-PC and DUMPtec are registered trademarks or registered trademarks of their respective owners. DIMM-PC and DUMPtec are registered trademarks or registered trademarks or registered trademarks of their respective owners. DIMM-PC and DUMPtec are registered trademarks or registered trademarks or registered trademarks or registered trademarks or their respective owners.

### > Technical Data

Processor

AMD Athlon™64 & AMD Phenom™ Single to Quad Core

hipset

AMD RS780 + SB700 Chipset with Hyperflash support for fast OS boot

BIOS

AMI®

Power Managemen

ACPI 3.0

Bus

4x PCI connector

1x PCI-Express 16x 2.0 Support

1x PCI Express 4x

DRAM

Up to 32GB of memory with ECC support for increased datasecurity

Graphics

Integrated version of ATI Radeon™ HD 3200 Graphics Core

Resolution

Up to: CRT 2048x1536, DVI 1600x1200 including 16x9 support

Graphic Interfaces

On board CRT, PCI-Express x16, DVI-D, HDMI (optional)

HDD

6x Serial ATA150/300 and 1x PATA 133 (2.54 mm connector)

Parallel Port

Bi-directional w. SPP, ECP or EPP mode, shared floppy drive option (internal pin connector)

Serial Port

2x RS232C serial ports with FIFO

RAID

HDD RAID 0/1/5/10

USB

12x USB 2.0 (6x internal and 6x external)

thernet

Up to 2x 10/100/1000 Ethernet Controller, Marvel 88E8055

Keyboard/Mous

Standard PS/2 mouse and keyboard (internal connection available)

Sound

HD Audio

Hardware Monitorir

Temperature, fan and voltages

Monitoring API/DN

Software interface to monitor hardware values including HDD S.M.A.R.T.

Battery

On board Lithium battery and external battery input

Operating Temp.

0-50°C

EMC/ESD compliance

Compliance with EN55022 and EN61000-4-2 (ESD)

Safety compliance

UL609501-1:2003, First edition

CSA C22.2 No. 60950-1-03, First edition, April 1. 2003

Environmental compliance

RoHS and Lead-free production

Dimensions

ATX, 300.5 mm x 243.8 mm (12" x 9,6")

Power Supply

ATX & BTX

## Ordering Information

Article	PartNo.	Description
KT780/ATX	810300-4500	KT780 with AMD Core and integrated ATI Radeon™ HD 3200 graphics

# ➤ Corporate Offices

**Europe, Middle East & Africa** Oskar-von-Miller-Str. 1 85386 Eching/Munich

Tel.: +49 (0)8165/ 77 777 Fax: +49 (0)8165/ 77 219 sales@kontron.com

Germany

North America

14118 Stowe Drive Poway, CA 92064-7147 USA

Tel.: +1 888 294 4558 Fax: +1 858 677 0898 sales@us.kontron.com **Asia Pacific** 

17 Building, Block #1, ABP. 188 Southern West 4th Ring Road Beijing 100070, P.R. China Tel.: + 86 10 63751188

Fax: + 86 10 83682438 kcn@kontron.cn Kontron Technology A/S

Dr. Neergaards Vej 5D 2970 Hørsholm **Denmark** 

Tel.: +45 4576 1016 Fax: +45 4576 1017 sales@kontron.com

