


SBC

PMB-585LF

Intel® Atom™ Mini ITX MB
w/VGA/LVDS/Audio/LAN

Features and Benefits:

- Intel® Atom™ N270 (1.6GHz) CPU on board
- Intel® 945GSE + ICH7M+ FWH (FSB: 533MHz)
- 1 x 200-Pin DDR2 SO-DIMM, supports DDR2 400/533 up to 2GB
- Fanless Solution



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
TEL: +1-714- 996-7200 FAX: +1-714- 996-7300
Sales: sales@protech-usa.net
<http://www.protech-usa.net>

Protech Japan Co., Ltd.


OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
<http://www.protech-j.com>



ISO CERTIFIED
9001 14001

PMB-585LF

Intel® Atom™ Mini ITX MB w/VGA/LVDS/Audio/LAN



Specifications

System	
CPU Support	Intel® Atom™ N270 (1.6GHz) CPU on board
CPU Frequency	1.6GHz
Chipset	Intel® 945GSE + ICH7M + FWH (FSB : 533MHz)
DRAM	1 x 200-Pin DDR2 SO-DIMM, supports DDR2 400/533 up to 2GB
BIOS	Phoenix-Award PnP BIOS, with VGA BIOS
Watchdog	1~255 secs Watchdog timer selectable w / Reset / NMI
Power Supply	Supports ATX
Power Requirement	+5V, +12V
Dimension	170mm x 170 mm (6.69" x 6.69")
Certificate	FCC / CE

I/O Chipset

SATA Interface	2 x S-ATA II connector
SSD	1 x compact flash slot (IDE)
Expansion BUS	1 x PCI, 1 x Mini PCI
Serial Port	4 x COM port, COM 1/3/4 for RS-232, COM 2 for RS-232/422/485
Parallel Port	1 x parallel port (SPP/EPP/ECP)
Keyboard	Mini DIN Connector
Mouse	Mini DIN Connector
LAN	Dual Ports Lan 1: Realtek 8111DL GbE Lan 2: Realtek 8111DL GbE

Audio	High Definition Audio; Realtek ALC888 with Mic / Line-In / Line-Out
D/I/O	8in / 8out
USB	8 x USB 2.0

Display

Graphic	Build-in Intel® 945GSE 1 x VGA D-sub 15 pin-header 2 x LVDS connector
LCD Interface	LVDS1 : support 18-bit LVDS2 : support 24-bit

Environment

Operation Temp.	0°~60°C (32°~140°F)
Storage Temp.	-40°~85°C (-40°~185°F)
Humidity	Operation humidity 20~90%, Storage humidity 20~95%

Ordering Information

PMB-585LF	Intel® Atom™ Mini ITX MB w/ VGA/ 2LVDS/ Audio/ 2LAN/ 4COM
PMB-585LF-16203	Intel® Atom™ Mini ITX MB w/ VGA/ LVDS/ Audio/ LAN/ 2COM, w/o DIO

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in Sep. 2010.