

IKVM-1708 19" 1U Rackmount drawer with 17" LCD/ Keyboard/ Mouse, 8 port KVM switch



Main Features

- Allows users to control up to 8 computers directly from an integrated 1U console drawer to save RACK space.
- 17" TFT LCD display supporting 1280 x 1024 with 300 nits brightness
- Control up to 64 computers respectively via a Cascade (IKVM-1408) installation and auto-Sensing of Bank Position on Cascade installations.
- Convenient computer selection via intelligent On Screen Display (OSD) Menus, Hot Keys, or Manual PC Selectors
- Mouse port or touch pad can be easily used to control connected computers
- Hot Pluggable - add / remove computers without powering down the Switch
- RoHS Com

Packing List

- 1 x IKVM-1708
- 1 x QIG (quick installation guide)
- 1 x Flash Cable
- 1 x IKVM-CBS18
- 1 x External Power Adapter, DC 12V@4A
- 2 x Rackmount Bracket

Optional Accessories

- **IKVM-CBS18-RS**
1.8M KVM Cable, DB-15M ↔ DB-15M, 2 x MD-6M, RoHS
- **IKVM-CBS30-RS**
3M KVM Cable, DB-15M ↔ DB-15M, 2 x MD-6M, RoHS
- **IKVM-CBS48-RS**
4.8M KVM Cable, DB-15M ↔ DB-15M, 2 x MD-6M, RoHS



● IKVM-CBS Cable



- Convenient computer selection via intelligent On Screen Display (OSD) Menus, Hot Keys, or Manual PC Selectors



- Two self-click prevents the keyboard from sliding in shaking



- Upgradeable Firmware



- Provides LCD OSD (On Screen Display) function

Specifications

1U height designed to save rack space	
LCD size	17" high brightness TFT LCD
Number of Pixels	1280 (H) x 1024(V)
Brightness (cd/ m2)	300
LCD Color	16.2M
Pixel Pitch (mm)	0.264(H) x 0.264(V)
Contrast Ratio	500:1
View Angle	H: 70/70, V: 70/70
LCD MTBF	50000 hrs
LCD On-Screen Display	Yes
Construction material	Heavy-duty steel
Keyboard and Key Pad	106 key PS/2 keyboard with touch pad
Port Selection	OSD / Hot Key / Push Button
Computer Connections (Direct) / Port LEDs / Port Switch Button	8
Computer Connections (Cascading)	Max. 64 (with IKVM-1408)
Computer Port Connector	HDDDB15 Female (Keyboard, Mouse, VGA)
Flash Upgrade	Support Firmware Upgradeable
Power Supply	Power adaptor: DC 12V@4A
Temperature	0 - 40 deg. C in operating; -20 - 60 deg. C in storage
Humidity	0 - 80% RH, non-condensing
Depth (mm)	556
Net/ GW (kg)	13.8/ 16.8

Ordering Information

- **IKVM-1708B-[L]-RS**
19" 1U Rackmount drawer with 17" LCD / Keyboard / Mouse, 8 port KVM switch, RoHS

[L]: Language Code

EN: English, JP: Japanese, DE: German, FR: French, IT: Italian

RU: Russian, ES: Spanish, KR: Korean, CH: Chinese

* For other language keyboard, please contact supplier