

RDC-1158-C1

15" Eight Ports KVM



FEATURES

- Industrial grade-A LCD TFT active-matrix color panel
- On-Screen Display allows for easy adjustment of color, brightness, contrast, position, and shape of the display
- Standard D-sub 15-pin VGA input connector
- Space saving design - ultra-low 1U (1.75") flip-up display enclosure
- Unique mechanical design to maximize mountable space
- Come with sliding rail and mounting kit for easy to integrate in any 19" cabinet
- Supports AT/XT, PS/2, UNIX, Sun, and Macintosh

ORDERING GUIDE

Standard

RDC-1158-C1

15" single port KVM

GENERAL

| | |
|---------------------------------|---|
| Display area | 304.1 (H) x 228.1 (V) (15.0-inch diagonal) |
| Pixel Pitch | 0.297 (H) x 0.297 (V) |
| Number of Pixels | 1024 (H) X768 (V) |
| Contrast Ratio | 350:1 |
| Color | 262,144(6bit/colors) |
| Brightness (cd/m ²) | 250 (Typ.) |
| On-Screen Display | Contrast, Brightness, H/V Position, H/V Size, H-scaling, Auto-adjust, Color Temp.(9300, 6500, User), Red-Gain, Blue-Gain, Green-Gain, Gamma, Recall, Phase, Channel, OSD exit |
| Power Consumption | Power Consumption: 30 Watts |
| Power Supply | Power Supply: AC 100-240V Universal |
| Power | 12VDC adapter |
| Input Signal | RGB Analog |
| VGA | 15-pin D-Sub |
| Keyboard / Mouse | PS/2 |
| Keyboard / Keypad | 88-key keyboard and integrated Touch Pad |
| Numeric keys | 17-key numerical key pad |
| Hot Key Control | OSD Hot Key |
| Temperature | 0~50in operating; -20~60 in storage |
| Humidity | 10~85% in operating; 10-90% in storage |
| Dimensions | 19.68in(D) x 19.01in(W) x 1.7in(H) |
| Weight | 21.1lb/9.1kg |