

AR-M9939

Micro Box



Xfire.acrosser.com.tw

Features

Fanless Internet Security Platform with VIA CPU (Eden) , 3LAN(Bypass function for optional), Compact Flash(True IDE mode), COM, Mini-PCI & PCI Slot, no VGA

Fanless

2 USB 2.0

PXE

Micro Box

Mini PCI

HDD Bay

VIA Eden

3 LANs

CF

Auto-MDIX

Console Redirection

By-passed LAN

Network Security-Firewall/VPN

Specification

System:

CPU Grade	On-board VIA Eden 733 MHz CPU
BIOS	Award
System Chipset	Pro266T, 8235 CD

Memory:

Technology	266 DDR SDRAM
System Memory	Support 128MB (Option for 64MB, 256MB, 512MB)

Ethernet:

Interface	On-board 10/100Mbps
LAN chipsets	Broadcom x 3 (BCM-4410)
Connector	RJ-45 x3 (optional)

Drive Bay:

2.5" HDD	1 (option)
----------	------------

Cooling:

System FAN	1 (option)
CPU FAN	1 (option)

I/O Interface:

	Internal Interface	External Interface
USB		2 (USB 2.0)
Serial Port	1 x RS232/422/485 with pin-header	1 x RS232 external connector
Mini PCI Interface	1 (3.3V Mini PCI connecto)	
Expansion Interface		1 (32-bit PCI Expansion Slot)
GPIO	8 Independent I/O Lines, TTL level	
PS/2	Mouse x 1, Keyboard x 1	
IDE	On-board 2.00mm 44 pin-header; 2 connectors Supports Ultra DMA 33	
Control		Power Switch
Solid State Disk	1 (Compact Flash Type II)	

Management:

Indicator	1x Power LED, 1x Hard drive LED, 8 LEDs for Network connect as ACT and Link
-----------	---

Miscellaneous:

Watchdog Timer	Software programmable 60 seconds
Bypass	2 pairs bypass function(Optional)

Environment:

Operating Temperature	0 ~ 60°C (32 ~ 140 °F)
Storage Temperature	-20 ~ 80°C(-4 ~ 176 °F)
Operating Humidity	0 ~ 90% Relative humidity non-condensing
Power Requirement	+12V Input; 50W AC power Adapter, Input range 115V AC 60GHz ~ 230V AC 50Hz

Physical:

Dimension (WxDxH)	242mm x141mm x40mm(9.42" x5.55" x1.58")
-------------------	---

Ordering Information

Standard:

AR-M9939	Micro Box Internet Platform for VIA solution, 3 LANs, Compact Flash, and Mini-PCI
----------	---

Specifications are subject to change without notice.