

# ARK-3389

## Intel® Pentium® M /Celeron® M Compact System



### Features

- Built-in Ultra Low Voltage Intel® Celeron® or Low Voltage Intel Pentium® M processor
- Sealed construction with fanless operation
- Anti-Vibration to ensure maximum reliability
- Easy integration, easy maintenance, few parts, and wide input voltage range



### Specifications

Processor System	CPU	Intel uFCBGA 479-pin Ultra Low Voltage Celeron or Intel Pentium M Low Voltage Processor ULV Celeron M 1.0 GHz (0KB L2 Cache) LV Pentium M 1.4 GHz (1MB L2 Cache)
	System Chipset	Intel 852GM GMCH or Intel 855GME Chipset Intel ICH4 Chipset 400 MHz FSB
	BIOS	4-Mbit Flash BIOS, supports Plug & Play, APM 1.2
	System Memory	1 x 200-pin SODIMM socket, Supports DDR SDRAM up to 1 GB
	Graphics	Chipset
Memory		Dynamic Video Memory Allocation up to 64 MB
Interface		CRT Interface, 36-bit LVDS interface
Ethernet	Controller	Intel 82551QM 10/100Base-T Ethernet controller
Others	Serial Interface	1 x RS-232 port and 1 x RS-232/422/485 port
	USB Interface	1 x USB port, USB 2.0 Compliant
	Watchdog timer	255 levels timer interval, setup by software
	Keyboard/Mouse	Supports PS/2 Mouse and PS/2 Keyboard
Software Options		Windows XP Embedded, Windows 2000/XP
Storage	HDD	Supports drive bay space for 2.5" HDD
	SSD	Supports CompactFlash socket for type I/II CompactFlash disk
Mechanical	Construction	Aluminum housing
	Mounting	Din-Rail mounting, Desk/wall-mounting
	Dimensions (W x H x D)	264.5 x 69.2 x 137.25 mm (10.41" x 2.72" x 5.4")
	Weight	2 kg (4.4 lb)
Power	Power Consumption	Typical: 24 W, Max 36 W
	Input Voltage	12 Vdc ~ 24 Vdc, 12 Vdc @ 3 A, 24 Vdc @ 1.5 A
Environment	Operating Temperature	With Industrial Grade CompactFlash disk: -20 ~ 60° C With 2.5-inch hard disk 0 to 45° C
	Relative Humidity	95% @ 40° C (non-condensing)
	Vibration Loading During Operation	With CompactFlash disk: 5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 Oct./min, 1 hr/axis. With 2.5-inch hard disk: 1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 Oct./min,
	Shock During Operation	With CompactFlash disk: 50 G, IEC 60068-2-27, half sine, 11 ms duration With hard disk: 20 G, IEC 60068-2-27, half sine, 11 ms duration
	EMC	CE/FCC Class A, CCC, BSMI
	Safety Certifications	UL, CCC, BSMI, CE

Computer On Modules **1**

Embedded Single Board Computers **2**

Compact Embedded Computers **3**

Pre-configured Systems **4**

Industrial Motherboards **5**

Slot Single Board Computers **6**

Industrial Computer Chassis **7**

Industrial Computer Peripherals **8**

Panel PCs **9**

Display Solutions **10**

Digital Video Solutions **11**

Vehicle Mounted Computers **12**

Portable Computers **13**

M2M Modules **14**

Embedded Software Services **15**