

[Home](#) > [Products](#) > [IPC Panel PC](#)

UU-TOUCH / UT-22

Intel® 945GSE Atom™ N270 Processor 3.5" Motherboard

SATA

Fan
Fanless

Dual View

- Intel® Atom N270 (1.6 GHz) processor @ 533 MHz FSB
- 200-pin DDR2 400/533 SO-DIMM, maximum up to 2.0 GB
- Intel® 945GSE and ICH7M
- built-in Intel® extreme GMA 950 Technology
- Intel® 82574L Gigabit Ethernet
- Dual View
- Realtek® ALC888, 5.1Channel HD Audio
- Mini-PCI socket



DOWNLOAD



[Product Spec \[PDF\]](#)

[Manual & Drivers](#)

 **ADOBE READER**



[Free Adobe Reader](#)

[Specifications](#)

System	
CPU	▶ Onboard Intel FCBGA8 45nm Atom N270 Processor
FSB	▶ 533MHz
BIOS	▶ Award 16Mb SPI BIOS
System Chipset	▶ Intel 945GSE + ICH7-M Chipset
Real Time Clock	▶ Chipset integrated RTC with onboard lithium battery
System Memory	▶ One 200-pin SODIMM up to 2GB Single Channel DDR2 533 SDRAM, non-ECC
SSD	▶ One CompactFlash Type I/II socket
Watchdog Timer	▶ Reset: 1 sec. to 255 min. and 1 sec. or 1 min./step
H/W Status Monitor	▶ Monitoring temperatures, voltages, and cooling fan status. Auto throttling control when CPU overheats
Expansion	▶ 1 PCI (PCI Rev. 2.3 compliant), 1 Mini PCI-E
TPM	▶ Optional, TPM1.2 (Infineon TPM chip 9635 TT 1.2)
Wake up on LAN or Ring	▶ LAN (PME/RPL)
Display	
Chipset	▶ Intel 945GSE integrated Graphics Media Accelerator 950
Display Memory	▶ Intel DVMT 3.0 supports 224MB video memory
Dual Display	▶ VGA D-SUB 15Pin Supports up to QXGA (2048 x 1536) LVDS 22" (1680 x 1050)
VGA	▶ On board GMA 950 supports CRT resolutions up to QXGA
Touch Screen	▶ 5 Wire resistive touch screen
Audio	
Audio Codec	▶ Realtek ALC888, 5.1 + 2 CH Audio
Ethernet	
LAN 1	▶ Intel® 82574L Gigabit Ethernet
Back Panel I/O Port	
Back Panel I/O Port	▶ 1 PS/2 Keyboard 1 PS/2 Mouse 1 VGA port 1 COM ports (2 COM Expansion Bracket) 1 RJ45 ports 4 USB 2.0/1.1
Mechanical & Environmental	
Power	▶ Full range DC 9V ~ 24V input (8 ~ 30V is operative)
Operating Temperature	▶ 0 to 60°C (32 to 140°F)
Operating Humidity	▶ 0% to 90% relative humidity, non-condensing
Size (L x W)	▶ 374.6 (W) x 284 (H) x 39.6 (D) mm
Weight	▶ 3 Kg

Ordering Information

-
-
-

[<< back](#)

Copyright © 2010 BPS • All rights reserved.